acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

#### 1 Identification

· Product identifier

· Trade name: X-tra Slik Bead Lubricant

· Article number: 14-752, 14-753, 14-753PM

· Recommended use and restriction on use

· Recommended use:

Lubricant

Tire maintenance.

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

31 Incorporated

## 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: None.
- · Signal word: Not regulated.
- · Hazard statements: None.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Components: None in reportable quantities.

### 4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

· After eye contact:

Rinse opened eye for several minutes under running water.

Seek medical treatment in case of complaints.

· After swallowing:

(Cont'd. on page 2)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

(Cont'd. of page 1)

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- · Most important symptoms and effects, both acute and delayed: Nausea in case of ingestion.
- · **Danger:** No relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture No special measures required.
- Advice for firefighters
- Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information: No relevant information available.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Particular danger of slipping on leaked/spilled product.

- · Environmental precautions No special measures required.
- · Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

(Cont'd. on page 3)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

(Cont'd. of page 2)

· Specific end use(s) No relevant information available.

### 8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Exposure controls
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Not required under normal conditions of use.

For spills, respiratory protection may be advisable.

Protection of hands:

Not required under normal conditions of use.

Protection may be required for spills.

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection:

Not required under normal conditions of use.

Protection may be required for spills.

- Limitation and supervision of exposure into the environment No special requirements.
- · Risk management measures No special requirements.

Information on basic physical a	and chemical properties	
Appearance:	and chemical properties	
Form:	Liquid	
Color:	Not determined.	
Odor:	Not determined.	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	

(Cont'd. on page 4)

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

		(Cont'd. of page
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water	er): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Other information	No relevant information available.	

# 10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No relevant information available.
- · Incompatible materials No relevant information available.
- · Hazardous decomposition products Possible in traces.

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- Sensitization: No sensitizing effects known.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

(Cont'd. on page 5)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

(Cont'd. of page 4)

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): No relevant information available.
- Repeated dose toxicity: No relevant information available.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · **Mobility in soil:** No relevant information available.
- Additional ecological information
- · General notes: Generally not hazardous for water
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

(Cont'd. on page 6)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

(Cont'd. of page 5)

4 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.	
· Transport hazard class(es)	Trot rogulatou.	
· DOT, ADR, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	( II of Not applicable.	

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

(Cont'd. on page 7)

Page: 7/7

## **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 14, 2018 Revision: June 14, 2018

Trade name: X-tra Slik Bead Lubricant

(Cont'd. of page 6)

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients are listed.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration