

Race Car Air Jacks

Raise your car in seconds! The Allstar Air Jack system connects to your race car with included weld-on mounting rings or with ALL11305 bolt-on mount kit (sold separately) for simplified installation. System will support vehicles up to 3,000 lbs. Works with a nitrogen tank, requires a hi-pressure regulator and a minimum 400 PSI hose.

Part No.	Description
ALL11300	Complete Kit (15.25" Stroke

ALL11302.....Complete Kit (11.75" Stroke)

Kit Includes:

4 Lift Cylinders 4 Safety Props **Weld-On Mounting Rings** Air Coupling and Reciever Plumbing Kit



ALL11315......Air Jack Cylinder 11.75" Stroke ALL11316...... Air Jack Cylinder 15.25" Stroke ALL11317......Safety Prop For 11.75" Cylinder ALL11318...... Safety Prop For 15.25" Cylinder

ALL11305...... Aluminum Bolt-On Mount Kit (8 Split Mounts)

ALL11319...... Mounting Ring Kit ALL11310......Pressure Regulator

ALL11312......Premium Hose Kit

(35 ft. of 500 PSI hose and fittings to connect ALL11300 Air Jack system to ALL11310 regulator.)

ALL11320......Complete Plumbing Kit







ALL11319



REV082615