

How to Switch to Amber Daytime Running Light (DRL) for AlphaRex 03-06 Chevrolet Silverado/02-06 Avalanche (Without Body Cladding) Headlights

Table of Contents

- AMBER SWITCH PLUG LOCATION
- CONNECT THE AMBER SWITCH PLUGS
- COMPLETE THE SWITCH TO AMBER DRL & PARKING LIGHTS

Disclaimer: This installation article is a tutorial guide. By reading this article, you agree it is for reference only and AlphaRex USA and its distributors make no guarantee on the finished results. Under no circumstances whatsoever shall AlphaRex USA nor its distributors be liable for any damage, misuse or personal injuries. If you do not fully understand the installation procedure, it is highly recommended that you seek help from professional mechanics to do the installation.

This instruction guide is applicable to the following ALPHAREX headlight products:

03-06 Chevrolet Silverado | 02-06 Avalanche (without body cladding) NOVA-Series LED Projector Headlights (Alpha-Black) / SKU: 880254
03-06 Chevrolet Silverado | 02-06 Avalanche (without body cladding) NOVA-Series LED Projector Headlights (Chrome) / SKU: 880255
03-06 Chevrolet Silverado | 02-06 Avalanche (without body cladding) NOVA-Series LED Projector Headlights (Black) / SKU: 880256

In the product list, the NOVA-Series headlights designed for the 2003-06 Chevrolet Silverado | 2002-06 Avalanche offer an optional switch plug, allowing you to customize the color of the Daytime Running Lights (DRL) and Parking lights to Amber (Yellow). By default, these lights come in White from the factory.

Customers have the flexibility to choose Amber (Yellow color) based on their preference.

PLEASE NOTE: Once you have plugged in and switched to Amber, the color of the Daytime Running Lights (DRL) and Parking lights will remain in Amber (Yellow color).



AMBER SWITCH PLUG LOCATION

To access the amber switch plug and connector, open the dust cover (rubber seal) located at the back of each ALPHAREX headlight. Look inside to find the components for adjusting the amber settings.



(TOP) HEADLIGHT ASSEMBLY



(LOWER) HEADLIGHT ASSEMBLY



CONNECT THE AMBER SWITCH PLUGS

Connect the amber DRL plugs inside each headlight set, ensuring a secure and proper connection between them. DO NOT USE DIELECTRIC GREASE!



COMPLETE THE SWITCH TO AMBER DRL & PARKING LIGHTS

After plugging in the connection, reinstall the headlights onto the vehicle. Congratulations! You have successfully switched to Amber (Yellow color) Daytime Running Lights (DRL) and Parking lights.

