



Catalog Number S-8000 Series

Bolt-in and Snap-in Mounting Fuse Blocks:

For 1/4" x 1 1/4" fuses.

Construction: Blocks are molded flame retarded thermoplastic. Clips are spring-bronze.

Voltage Rating: 300Vac/dc

Agency Approvals:

UL Recognized under Components Program; File E14853, Guide IZLT2

CSA Certified Class 6225-01, File 47235

Anti-Rotation Pin: Single-pole blocks may be ordered without the antirotational pin simply by adding an "X" to the number of poles (Example: BK/S-8001-1X).

Carton Quantity: 10; shelf package: 100.

Bulk Carton: Single-pole and 2-pole fuse blocks — 1,000; Multiple-pole fuse blocks — 3-8 pole: 200; 9-12 pole: 50.

When ordering bulk quantities, prefix "BK/" to catalog number: (Example: BK/S-8001-1SNP).

Bolt-in Mounting

Series	Terminal	Amps	Angle	*Basic Cat. No.	Poles (Suffix)
S-8000	Solder	UL 25A CSA 21A	0° 40°	S-8001- S-8002-	1 - 12
S-8100	3/16" Quick Connect	UL 20A CSA 16A	0° 40°	S-8101- S-8102-	
S-8200	1/4" Quick Connect	UL 20A CSA 16A	0° 40° Side	S-8201- S-8202- S-8203-	
S-8301	Screw	UL 30A CSA 10A	—	S-8301-	

Snap-in Mounting (Poles available in single-pole only)

Series	Terminal	Amps	Angle	Cat. No.
S-8000	Solder	UL 25A CSA 21A	0° 40°	S-8001-1-SNP S-8002-1-SNP
S-8100	3/16" Quick Connect	UL 20A CSA 16A	0° 40°	S-8101-1-SNP S-8102-1-SNP
S-8200	1/4" Quick Connect	UL 20A CSA 16A	0° Side	S-8201-1-SNP S-8203-1-SNP

Catalog Part Number System

Prefix for Bulk Packing	BK/	S-8	0	00	-00	-SNP	-R
S-8000 Series							
Type Terminal	"0"-Solder; "1"-3/16" Quick Connect; "2"-1/4" Quick Connect; "3"-Screw						
Terminal Angle	"01"-straight (0); "02"-40°; "03"-side*						
Number of Poles (01-12)							
Snap-In							
RoHS							

* Available only in a single pole