

Installation Instructions

8891024 & 8891025 LED Dashboard Mount Strobe Lights



* 12-24V, 0.4 Amps @ 12V

Installation

Choose windshield location
Clean windshield and dashboard surface with alcohol
Loosen 2 sets of screws on each side and adjust tilt to match angle of windshield. Once correct angle is found, secure screws.

Choose mounting option:

1. Suction cup
2. Velcro

Attach light

Operation

Insert power plug into vehicle accessory power port
Push power on/off switch
Push flash pattern selector switch for next pattern

FP#	Flash Patterns
1	Random 1
2	Side-to-Side Alt. Single
3	Side-to-Side Alt. Double
4	Side-to-Side Alt. Triple
5	Side-to-Side Alt. Quint
6	Side-to-Side Alt. Hold
7	Side-to-Side Alt. Burst
8	Side-to-Side Alt. Mega
9	Side-to-Side Alt. Ultra
10	Synchro Flash
11	Synchro Flash Triple
12	Synchro Flash Mega
13	Synchro Flash Ultra 1
14	Synchro Flash Ultra 2
15	Random 2
16	Random 3
17	Steady DS, Dbl. Flash PS
18	Steady PS, Dbl. Flash DS
19	Off

WARNING

Do not block airbags with power cord.



8891025
Shown powered on

WARNING

Do not look directly into LEDs while in operation; this may cause momentary blindness and/or eye damage.