



CATALOG NUMBER: See table below
DESCRIPTION: Automotive battery booster cables with Polar-Glo clamps
APPROVALS: UL Listed

CONSTRUCTION PARAMETERS:

Cable length: See table below
 Conductor: See table below
 Insulation material: TPE
 Cable insulation color: See table below
 Cable legend type: Indent print
 Clamp material: PVC coated steel
 Contact jaw material: Copper plated steel
 Polarity indication: Red and black clamps, "+POS" and "-NEG" stamped into clamp handles, phosphorescent labels on clamp handles

ELECTRICAL PROPERTIES:

Cable temperature rating: -40 to +60 °C
 Maximum operating current: See table below



Catalog number	Cable gauge	Cable length	Conductor stranding	Current rating	Insulation color
08467	8 ga Cu equivalent	12 ft	49 / 0.0212 Cls 10A CCA	200 A	Yellow
08565	6 ga Cu equivalent	12 ft	77 / 0.0212 Cls 10A CCA	300 A	Orange
08566		16 ft		250 A	
08665	4 ga Cu equivalent	12 ft	126 / 0.0212 Cls 10A CCA	400 A	Red
08666		16 ft		350 A	
08660		20 ft		300 A	
08662		25 ft		250 A	

This product complies with European Directive 2011/65/EU (RoHS-2)

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company LLC.