


REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER LM14214	2014-05-22
A	INITIAL RELEASE PER LM14214	2014-06-02




SPECIFICATIONS

- CERTIFICATIONS: **CE**; ECE R10; SAE J845 (DEC 2007) CLASS 1 YELLOW (AMBER); CA Title 13 Class B; IP-35C For a Category 2 Enclosure

Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- FLASH MODE: DOUBLE : 75 ± 5 FLASHES PER MINUTE
QUAD : 75 ± 5 FLASHES PER MINUTE
QUINT : 75 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12 to 24 VDC
- VOLTAGE (EXTREME): 9.0 to 32.0 VDC
- CURRENT (PEAK): 6A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 76.8W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER ADAPTER ADAPTER
- MOUNTING: MAGNET
- BASE MATERIAL: POLYCARBONATE
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 4.5 LBS (2.03 Kg)



NOTES:
1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

SCALE 1:4.5		APPROVALS	DATE	ECCO®
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:02		DRAWN BY SNS	2014-05-22	
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		CHECKED BND	2014-05-23	
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	MECH. ENG. NMT	2014-05-30	LED MINIBAR, 8 HEAD, 12-24VDC, A, C1, MG
	ANGLES ± 0.5° FRACTIONS ± 1/64	ELEC. ENG. TJT	2014-05-22	
		TEST ENG. JRT	2014-05-30	CUSTOMER PART NO. 5590A-MG
		SALES. LAT	2014-05-27	PRODUCT SERIES: 5500
NON DISCLOSURE AGREEMENT				SIZE: A
THIRD ANGLE PROJECTION				DWG. NO. 5590A-MG
		Electronically Controlled Use Latest Copy		REV. A
		SHEET 1 OF 1		Project: LM14214
		Date Created: 2014-05-13		