

	REVISION HISTORY				
REV.	DESCRIPTION	DATE			
01	PRELIMINARY RELEASE PER EP0020				
02	REVISED PER EP0020	2017-06-12			
Α	INITIAL RELEASE PER EP0020	2017-06-16			

15'[4572] CORD W/ DUAL SWITCH LIGHTER ADAPTER

SPECIFICATIONS

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

2. FLASH MODE: DOUBLE: 75 ± 5 FLASHES PER MINUTE

QUAD : 75 ± 5 FLASHES PER MINUTE QUINT : 75 ± 5 FLASHES PER MINUTE

- 3. VOLTAGE (NOMINAL): 12-24 VDC
- 4. VOLTAGE (EXTREME): 9-32 VDC
- 5. CURRENT (PEAK): 6A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 76.8W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 8. CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER ADAPTER
- 9. MOUNTING: ADHESIVE
- 10. BASE MATERIAL: POLYCARBONATE11. LENS MATERIAL: POLYCARBONATE12. PRODUCT WEIGHT: 6.5 LBS (2.93 Kg)

COLOR CHART		
FGS P/N	COLOR	
5590CA-HBT	AMBER	

NOTES:

1. ROHS COMPLIANT

9.0 229

2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT	
LOSES ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO. AND IS ISSUED IN CONFIDENCE FOR	- A

CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: 01				DRAWN BY		2017-06-12
				CHECKED	ABD	2017-06-12
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	NMT	2017-06-13	
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES • 0.5	ELEC. ENG.		
	XX. ± 1.0mm XX.X ± 0.5mm	X.XX ± 0.04	FRACTIONS	TEST ENG.	JRT	2017-06-12
X.XXX ± 0.02 ± 1/64 THIRD ANGLE PROJECTION			SALES.	ARS	2017-06-12	
1	$\mathcal{L}_{\mathcal{L}}$		1			

APPROVALS

SCALE 1:6



LED MINIBAR,8 HEAD,12-24VDC,C1,HBT

2017-06-12 CUSTOMER PART NO. SEE CHART

SIZE: A DWG. NO. 5590CX-HBT

Electronically Controlled Use Latest Copy | SHEET | OF | Project: EP0020 | Date Created: 2017-06-07