

## **BACK-UP ALARMS**

# 575 SERIES

The 575 Series provides a high dB(A) alarm in a compact housing for use in less arduous environments where ambient noise level is high. ECCO specifically designed these products to meet our quality standards, yet provide a cost-considerate product. The reinforced nylon housing provides rugged durability and the epoxy-encapsulated circuit board protects the electronics from vibration and moisture. ECCO's unique grill design meets the requirements of SAE J994 for high-pressure washing. The 575 provides a high dB(A) alarm with exceptional reliability at a reasonable cost.

#### Models

PART NO.	VOLTAGE	dB(A)
575	12-24	107

AMPS 0.9 APPROVALS SAE Type B, CE, R10 UL

#### **Features and Benefits**

- · Compact size and universal mounting bracket maximizes location options
- Reverse polarity, voltage spike and surge protected
- Works on positive and negative ground systems
- Epoxy sealed to protect against dust, moisture and vibration
- Temperature Range: -40°F to +185°F (-40°C to +85°C)
- 2 Year Warranty

2.8 [72] 2.8 [72] 3.25 [83] 4.0 [102]

### **Alarm Specifications**

Connection: 16 AWG blunt cut wires Reinforced nylon housing Recommended mounting bolt: 1/4" Grade 5 Recommended washer: 1/4" Type A, Series N or W Recommended mounting torque: 76 in. lbs.