

REVISION HISTORY					
REV.	DESCRIPTION	DATE			
G	REVISED PER P08054	2011-05-25			
Н	REVISE PER P08054	2011-09-23			
J	REVISE PER EC4447	2017-08-01			

3-16 AWG WIRES RED: POSITIVE (+) BLK: NEGATIVE (-) WHT: DUAL/QUAD

LENS CHART					
PRODUCT P/N	LENS COLOR				
6550A	AMBER				
6550B	BLUE				
6550C	CLEAR				

SPECIFICATIONS

1. CERTIFICATIONS: SAE J1318 (MAY 1998), CLASS 2, YELLOW (AMBER) BLUE, WHITE (CLEAR)COLORS;

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols.

Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. FLASH MODE: DOUBLE : 80 ± 5 FLASHES PER MINUTE QUAD : 65 ± 5 FLASHES PER MINUTE
- 3. VOLTAGE (NOMINAL): 12 to 48 VDC4. VOLTAGE (EXTREME): 9.0 to 56.0 VDC
- 5. CURRENT (PEAK): 2.4A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 30W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 8. CONNECTION: 3-16 AWG WIRES
- 9. MOUNTING: FLANGE MOUNT, PIPE MOUNT
- 10. BASE MATERIAL: GLASS FILLED NYLON
- 11. LENS MATERIAL: POLYCARBONATE
- 12. PRODUCT WEIGHT: 1.2 LBS (0.54 Kg)

 4.9 [124]	
	

NOTES: 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THIS DRAWING AND THE DESIGN IT DISCLOSE ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO, AND IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRICA WRITTEN CONSENT OF ELECTRONIC CONTROLS CO, THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTIANCE OF THESE TERM, 1998 ELECTRONIC CONTROLS CO.

	SCALE 1:2.5			APP	ROVALS	DATE	
		GENERATED DRA		DRAWN BY		2017-06-13	
	DO NOT MANUALLY UPDATE. MODEL REFERENCED: G TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			CHECKED	ABB	2017-06-14	7 K
				MECH. ENG.	KLR	2017-06-14	
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	SPO	2017-06-16	
	XX. ± 1.0mm XX.X ± 0.5mm	1.0mm X.X ± 0.1 0.5mm X.XX ± 0.04 FRAC	FRACTIONS	TEST ENG.	JRT	2017-06-19	CUST
_	X.XXX ± 0.02 ± 1/64 THIRD ANGLE PROJECTION			SALES.	ARS	2017-06-20	SE
			1				SIZE:

ECC) *
------------	------------

STROBE,360*,12-48 VDC,7/10JOULES
TOMER PART NO. PRODUCT SERIES: