


BACK-UP ALARMS

800 SERIES OEM Mounting Pattern

Designed to meet all the harsh operational requirements of any fleets equipment, ECCO's 800 Series alarms feature a reverse-mounted speaker design and reinforced nylon housing providing unrivaled durability. These alarms are so robust that an ECCOLIFE™ warranty covering the alarm for the life of the vehicle is offered on all models. These 800 Series alarm models feature a mounting bracket with the same mounting pattern popular with OEM's. Smart Alarm® models measure ambient noise and adjust their sound level, creating a volume that is safe without being annoying or contributing to noise pollution. Smart Alarms eliminate the need for constant manual adjustment and help prevent intentional alarm disconnection.



Models

PART NO.		VOLTAGE	dB(A)	AMPS	APPROVALS
SA914N	SMART)	12-24	87-112	1.5	SAE Type F, CE, R10
876N		12-36	112	1.3	SAE Type A, CE, R10, UL, AMECA
872N		12-36	97/112	1.4	CE, R10

Features and Benefits

- · Mounting backet features popular OEM footprint
- Reverse-mounted speaker enhances sound and protects the speaker from dust and moisture ingress
- Reinforced nylon housing eliminates corrosion damage
- Sealed in epoxy for protection against dust, moisture and vibration
- Temperature Range: -40°F to +185°F (-40°C to +85°C)
- ECCOLIFETM Warranty

Alarm Specifications

Connection: 16 AWG blunt cut wires

Reinforced nylon housing Recommended mounting bolt:

Bottom: 3/8-16 UNC Grade 5 or better

Recommended washer:

Bottom: 3/8" Type A Series N washer Recommended mounting torque:

Bottom: 276 in. lbs.