


REVISION HISTORY		
REV.	DESCRIPTION	DATE
04	REVISED PER EL0145	2019-08-16
A	INITIAL RELEASE PER EL0145	2019-08-19
B	REVISED PER EL0145	2019-12-18



2 x ϕ 0.33 [9]
MOUNTING HOLES

TOP VIEW



FRONT VIEW

SPECIFICATIONS

- CERTIFICATIONS: **CE**; IP67, IP69K
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- RAW LUMENS: 3460 lumens
- EFFECTIVE LUMENS: 3326 lumens
- ILLUMINANCE (@100 FT): 78.6 lux
- PEAK BEAM INTENSITY: 73170 candela
- VOLTAGE (NOMINAL): 12-24 VDC
- VOLTAGE (EXTREME): 10-30 VDC
- CURRENT (PEAK): 3A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 40.8W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -40°F (-40°C) TO 158°F (70°C)
- CONNECTION: 2 - 16 AWG WIRES
- MOUNTING: BRACKET
- HOUSING MATERIAL: ALUMINUM, BLACK COATING
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 4.42 LBS (1.99 Kg)

MOUNTING DISCLAIMER

MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

DISCLAIMER

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS, AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

- NOTES:
- CABLE NOT SHOWN FOR CLARITY
 - CABLE DIMENSION WITH DEUTSCH CONNECTOR IS 31.50 ± 1.00 [800 ± 25] FROM THE WIRE EXIT TO THE END OF MATING CABLE
 - DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THEREIN. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2019 ELECTRONIC CONTROLS COMPANY

SCALE 1:4		APPROVALS	DATE	
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: 01		DRAWN BY ABD	2019-12-06	
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		CHECKED MDH	2019-12-09	
MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES	MECH. ENG.	UTILITY BAR, LED, 32", SINGLE, COMBO, 12-24V CUSTOMER PART NO. EW3132 PRODUCT SERIES: EW3100
XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS ± 1/64	ELEC. ENG. SPO	
THIRD ANGLE PROJECTION			TEST ENG. RM	
		SALES. ARS	2019-12-09	SIZE: B
		Electronically Controlled Use Latest Copy		DWG. NO. EW3132
		SHEET 1 OF 1		REV. B
		Project: EL0145		Date Created: 2019-04-03