



ENEOS Gear Oil GL-5 75W-90

DESCRIPTION

ENEOS Gear Oil GL-5 75W-90 is a high performance gear oil using the latest sulphur-phosphorus technology. This additive technology assures an excellent protection of the gears against metal-to-metal contact under the most severe conditions, even under shock-loads. ENEOS Gear Oil is recommended for use in bevel, spiral bevel and hypoid gear type differentials and in power dividers compatible with synchromesh; ensures easy and smooth shifting even at very low temperatures.

APPLICATION

ENEOS Gear Oil GL-5 75W-90 is recommended for uses in manual transmissions and non-limited differentials including heavy-duty manual transmissions, axles and final drives which require API GL-5 and 75W-90 viscosity.

Note: Please consult your vehicle owners' manual for proper transmission fluid requirements.

TYPICAL PROPERTIES

ENEOS [Gear Oil](#) GL-5 75W-90

Test Item	Data	Test Method
API Grade	GL-5	
SAE Viscosity	75W-90	
Color	L0.5	
Density (15°C) g/cm ³	0.887	ASTM D 4052
Viscosity mm ² /s		ASTM D 445
(40°C)	78.8	
(100°C)	14.5	
Viscosity Index	193	ASTM D 2270
Flash Point °C	194	ASTM D 92
Pour Point °C	-40	ASTM D 97
Acid Number mgKOH/g	1.04	ASTM D 664

Note: Typical Properties are test data to be expected in normal production and subject to change without notice.