



INSTALLATION INSTRUCTIONS

**2017 FORD F250/350 4WD
6" BASIC SYSTEM**

FTS22218

- PARTS LIST -

| FTS22024BK 6" FORD F250/350 FRONT COILS | | |
|--|-----------|---------------|
| 2 | FT30123BK | 6" FRONT COIL |

| FTS22250 6" FORD F250/350 FRONT GAS COILS | | |
|--|---------|---------------|
| 2 | FT30732 | 6" FRONT COIL |

| FTS22218 6" BASIC SYSTEM | | |
|---------------------------------|---------|----------------------------------|
| 1 | FT30122 | PITMAN ARM |
| 2 | FT30654 | 6" BUMP STOP EXT |
| 2 | FT30651 | RADIUS ARM DROP |
| 1 | FT30724 | TRAC BAR DROP BRACKET |
| 1 | FT30687 | HARDWARE KIT |
| 1 | FT30674 | HARDWARE SUBASSEMBLY |
| 1 | FT30672 | STEERING STABILIZER BRACKET |
| 1 | FT30686 | STEERING STABILIZER CLEVIS MOUNT |
| 1 | FT30630 | SWAY BAR DROP (DRIVER) |
| 1 | FT30629 | SWAY BAR DROP (PASSENGER) |

| FTS22219 6" REAR BOX KIT | | |
|---------------------------------|---------|--------------------------------|
| 4 | FT742U | UBOLT RD 5/8-18 X 18.00 X 3.50 |
| 1 | FTBK54D | BLOCK (DRIVER) |
| 1 | FTBK54P | BLOCK (PASSENGER) |
| 1 | FT58H | 5/8" UBOLT HARDWARE KIT |

| K2217 6" BASIC SYSTEM W/PERFORMANCE SHOCKS | | |
|---|----------|---------------------------|
| 1 | FTS22219 | 6" BASIC SYSTEM BOX |
| 1 | FTS22218 | 6" REAR BOX KIT |
| 2 | FTS7188 | PERFORMANCE SHOCK (FRONT) |
| 2 | FTS7266 | PERFORMANCE SHOCK (REAR) |

| K2217M 6" BASIC SYSTEM W/ STEALTH SHOCKS | | |
|---|----------|--------------------------------|
| 1 | FTS22219 | 6" BASIC SYSTEM BOX |
| 1 | FTS22218 | 6" REAR BOX KIT |
| 2 | FTS6188 | STEALTH MONOTUBE SHOCK (FRONT) |
| 2 | FTS6063 | STEALTH MONOTUBE SHOCK (REAR) |

| K2217DL 6" BASIC SYSTEM W/ DLSS SHOCKS | | |
|---|-----------|--------------------------------|
| 1 | FTS22219 | 6" BASIC SYSTEM BOX |
| 1 | FTS22218 | 6" REAR BOX KIT |
| 2 | FTS810382 | 2.25 DIRT LOGIC SS N/R (FRONT) |
| 2 | FTS810052 | 2.25 DIRT LOGIC SS N/R (REAR) |

| FT30674 HARDWARE SUBASSEMBLY | | |
|-------------------------------------|-----------|------------------------------|
| 1 | FT22218i | INSTRUCTIONS |
| 1 | FT30258 | SECTOR SHAFT NUT |
| 2 | FT30660 | BRAKE LINE TAB |
| 2 | FT50290 | BUMP STOP NUT TAB |
| 1 | FT30604 | SPACER |
| 1 | FTAS12 | STICKER FT BLUE 10X4 DIE CUT |
| 1 | FTAS16 | DRIVER WARNING DECAL |
| 1 | FTREGCARD | REGISTRATION CARD |

| FT30687- HARDWARE KIT | | LOCATION |
|------------------------------|-------------------------------|---------------------|
| 8 | 7/16 SAE WASHER G8 ZINC | SWAY BAR |
| 4 | 7/16-14 C-LOCK NUT ZINC | |
| 4 | 7/16-14 X 1 1/4 HEX HD | |
| 2 | 3/8-16 X 1" HEX BOLT | BRAKE LINE |
| 4 | 3/8" SAE WASHER | |
| 2 | 3/8-16 NYLOCK NUT | |
| 2 | 1/4 SAE WASHER | |
| 1 | 1/4-20 GR C CROWNLOCK NUT | |
| 1 | 1/4-20 X 3/4 HEX BOLT G5 ZINC | |
| 2 | 1/2-13 X 1-1/4 HEX BOLT | BUMP STOP |
| 2 | 1/2-13 X 1-1/2 HEX BOLT | |
| 6 | 1/2 SAE WASHER | |
| 2 | 1/2-13 C-LOCK NUT | |
| 8 | 3/4-10 X 1-1/2" HEX BOLT | RADIUS ARM DROP |
| 16 | 3/4 SAE WASHER | |
| 8 | 3/4-10 C-LOCK NUT | |
| 1 | COTTER PIN | |
| 1 | M12-1.75 X 70MM HEX BOLT | STEERING STABILIZER |
| 2 | M12 WASHER | |
| 1 | M12-1.75 C-LOCK | |
| 1 | 9/16-12 NYLOCK NUT | |
| 3 | 9/16 SAE WASHER | |
| 1 | THREAD LOCKING COMPOUND 1 MIL | |
| 1 | HOSE CLAMP | |

- TOOL LIST -

Required Tools (Not Included)

- Basic Hand Tools
- Assorted Metric and S.A.E sockets, and Allen wrenches
- Torque Wrench
- Die Grinder w/ Cutoff Wheel or Sawzall
- 1-1/4" Hole Saw
- Basic Hand Tools
- Floor Jack
- Jack Stands
- Drill

- PRE-INSTALLATION NOTES -

READ THIS BEFORE YOU BEGIN INSTALLATION -

Check all parts to the parts list above before beginning installation.

Read all instructions thoroughly from start to finish before beginning the installation. If these instructions are not properly followed severe frame, driveline and / or suspension damage may occur.

Check your local city and state laws prior to the installation of this system for legality. Do not install if not legal in your area.

Prior to the installation of this suspension system perform a front end alignment and record. Do not install this system if the vehicle alignment is not within factory specifications. Check for frame and suspension damage prior to installation.

The installation of this suspension system should be performed by two professional mechanics.

This suspension must be installed with Fabtech shock absorbers.

Use the provided thread locking compound on all hardware.

WARNING- Installation of this system will alter the center of gravity of the vehicle and may increase roll over as compared to stock.

Vehicles that receive oversized tires should check ball joints, uniballs, tie rods ends, pitman arm and idler arm every 2500-5000 miles for wear and replace as needed.

Verify differential fluid is at manufactures recommended level prior to kit installation. Installation of the kit will reposition the differential and the fill plug hole may be in a different position. (For example, if the manufacture recommends 3 quarts of fluid, make sure the diff has 3 quarts of fluid). Check your specific manual for correct amount of fluid.

Recommend Tires and Wheels:

- Use 37/12.50R18 tire w/ 18x9 wheels w/ 4-3/4" BS w/ required fender well trimming
- Use 37/13.50R20 tire w/ 20x9 wheels w/ 5" BS w/ required fender well trimming

FOOTNOTES -

- NON DUALY MODELS ONLY
- WILL NOT FIT GAS MOTORS
- VEHICLES EQUIPPED WITH 2 PIECE REAR DRIVE SHAFT REQUIRE PART #FTS419
- VEHICLES W/ FACTORY REAR SWAY BAR MUST ORDER EXTENDED SWAY BAR LINK KIT PART NUMBER FTS22276.
- SOME 2017 MODELS MAY REQUIRE A DUAL STEERING STABILIZER TO ADDRESS STEERING FEEDBACK. ORDER DIRT LOGIC-FTS220512, DIRT LOGIC W/RESI-FTS221162 OR STEALTH-FTS8046

- INSTRUCTIONS -

FRONT SUSPENSION

1. Disconnect the negative terminal on the battery. Jack up the front end of the truck and support the frame rails with jack stands. **NEVER WORK UNDER AN UNSUPPORTED VEHICLE!** Remove the front tires.
2. Disconnect the sway bar from the sway bar end links and frame. Remove sway bar. Save hardware. **SEE FIGURE 1**



FIGURE 1 - STEP 2

3. Disconnect the brake line from the frame and axle on both driver and passenger sides. Save hardware. **SEE FIGURES 2-3**




FIGURE 2 - STEP 3



FIGURE 3 - STEP 3

4. Remove the front shocks and discard, save hardware.
5. Lower the front axle allowing the coil springs to come free of tension and remove the coil springs. **EXERCISE EXTREME CAUTION WHEN WORKING WITH COIL SPRINGS UNDER LOAD!**
6. Disconnect the factory steering stabilizer from the frame mount. Remove the steering stabilizer frame bracket. Discard the frame bracket. Save all hardware.
7. Remove the drag link from the pitman arm. **Use care not to damage the threads on the drag link.**
8. Disconnect the trac bar from the frame bracket. Remove the trac bar bracket from the frame, save the original hardware and discard the factory trac bar bracket.
9. Remove the factory pitman arm from the steering box using a large pitman arm puller. Discard hardware and arm.
10. Install FT30122 (Pitman Arm) using the supplied FT30258 (Sector shaft nut). Torque to 350 ft-lbs. **NOTE: This is a one time only use nut. If remove, it must be discarded.**
11. Locate FT30724 (Track Bar Bracket). Attach to the frame using the original hardware in the same position. Torque bolts to 120 ft-lbs. **DO NOT ATTACH THE TRACK BAR TO THE FRAME BRACKET AT THIS TIME. SEE FIGURES 4-5**



FIGURE 4 - STEP 11




FIGURE 5 - STEP 11

12. Working from both sides of the truck, locate and remove the factory front bump stops and save. Pull on the bump stop itself to free from the cup. Remove the factory mounting cup from the frame and discard the hardware. Drill out the center hole on the factory cup to 1/2". **SEE FIGURES 6-7**




FIGURE 6 - STEP 12



FIGURE 7 - STEP 12

13. Install FT30654 (Bump Stop Extension) onto the factory cup using the supplied 1/2" x 1-1/4" hardware and set aside. Torque to 127 ft-lbs. **SEE FIGURE 8**




FIGURE 8 - STEP 13

14. Locate the factory bump stop mounting hole. Measure 3" straight up from the bottom of the frame. Mark and drill a 1-1/4" hole using a hole saw into the frame. **SEE FIGURES 9-10**





FIGURE 9 - STEP 14




FIGURE 10 - STEP 14

15. Drill out the factory bump stop mount hole to 1/2". **SEE FIGURE 11**




16. Using FT50290 (Nut Tab) and 1/2 X 1-1/2" bolt and washer. Mount the new bump stop extension to the frame. Route the Nut tab through the 1-1/4" hole that was made in Step 11. Torque to 127 ft-lbs. **SEE FIGURE 12**




REPEAT BUMP STOP INSTALLATION ON PASSENGER SIDE

17. With the front axle still supported by the floor jack, disconnect the factory radius arm from the factory frame mounts. Remove the upper bolt at the axle and allow the radius arm to hang. Save the factory hardware.

18. Install FT30651 (radius arm drop brackets). Place the brackets into the factory radius arm pockets. Attach the bracket to the factory bracket using the supplied 3/4" x 1-1/2" bolts, nuts and washers through the original holes in the frame. Torque bolts to 450 ft-lbs. **SEE FIGURE 13**




19. Reinstall the radius arm into the new drop down bracket using the factory hardware. Attach to the axle first then to the new drop bracket using the lower hole. Torque to 300 ft-lbs. **SEE FIGURE 14**



- **REPEAT STEPS 17-19 ON PASSENGER SIDE**
- **IF INSTALLING A COILOVER CONVERSION KIT DO SO NOW THEN SKIP TO STEP 22**

20. Install FT30123BK (Coil Spring) using the factory upper isolator. **SEE FIGURE 15**



21. Install the new front shocks FTS7188, FTS6188 or FTS810382 with the supplied bushing kits. Using the factory hardware. **NOTE: Install a supplied 9/16" washer at the lower mount to fill up the gap between the bushing and mount.** Due to vehicle variances the top of the lower shock mount may need to be sanded down to clear the shock body only if installing Stealth shocks. **SEE FIGURE ON LAST PAGE.**
22. Reinstall the track bar to the new frame bracket. Torque to 400 ft-lbs. Install the drag link to the new Fabtech pitman arm using the factory hardware and the new supplied cotter pin. Torque to 70 ft-lbs. **NOTE: The drag link will need to be rotated 180 degrees and installed from the bottom side of the pitman arm. SEE FIGURE 16**



23. **(DRIVER SIDE)** Install FT30660 (Brake line bracket) to the factory brake line tab using the supplied 3/8" hardware. Next, install the bracket to the frame using the factory hardware. Torque hardware to 52 ft-lbs. **SEE FIGURE 17**



24. **(PASSENGER SIDE)** Install FT30660 (Brake line bracket) to the factory brake line tab using the supplied 3/8" hardware (Use lower hole). Next, using the supplied rubber clamp and 1/4" hardware, attach the ABS line to the upper hole on the FT30660 bracket. Re attach to the frame using the factory hardware. Torque 3/8" & factory hardware to 52 ft-lbs. Torque 1/4" hardware to 14 ft-lbs. **SEE FIGURE 18**



25. Install FT30672 (steering stabilizer drop bracket) in the factory location using the factory hardware. Torque to 127 ft-lbs. **SEE FIGURE 19**




FIGURE 19 - STEP 25

26. Install FT30686 (Stabilizer Clevis) on the factory steering stabilizer using the supplied M12 hardware. **NOTE: Install FT30604 (spacer) like shown in the figure below.** Install the stabilizer using the supplied 1/2" washer and nut to the drag link. Using the factory hardware install the tapered end into the new Fabtech bracket. Torque to 127 ft-lbs. **SEE FIGURE 20**




FIGURE 20 - STEP 26

27. Install FT30630 (Driver) & FT30629 (Passenger) Sway bar drop brackets using the factory hardware. Reinstall the front sway bar to the end links using the supplied 7/16" hardware torque all hardware to 83 ft-lbs. Reconnect the sway bar to the end links. Torque to 52 ft-lbs **SEE FIGURE 21**




FIGURE 21 - STEP 27

28. Install the lower brake line bracket to the lower spring perch using the factory hardware. Torque to 29 ft-lbs.
29. Install the front tires and wheels. Torque lug nuts to wheel manufacturer's specifications.

REAR SUSPENSION

30. Locate and install the rear lift blocks FTBK54D & P. The factory block will need to be removed. The short end of the blocks should face to the front of the vehicle. Using the supplied u-bolts, nuts and washers align axle, lift blocks and springs and torque to U-Bolts to 170 ft-lbs. **SEE FIGURE 22**




FIGURE 22 - STEP 30

31. Install the new rear shocks FTS7266, FTS6063 or DL FTS810052 using the factory hardware, torque to 90 ft-lbs.
32. Install tires and wheels and torque lug nuts to wheel manufacturer's specifications. Turn front tires left to right and check for appropriate tire clearance. **Note - Some oversized tires may require trimming of the front bumper & valance.**
33. Check front end alignment and set to factory specifications. Readjust headlights.
34. Recheck all bolts for proper torque.
35. Recheck brake hoses, ABS wires and suspension parts for proper tire clearance while turning tires fully left to right.
36. Check the fluid in the front and rear differential and fill if needed with factory specification differential oil. **Note - some differentials may expel fluid after filling and driving. This can be normal in resetting the fluid level with the new position of the differential/s.**
37. Install Driver Warning Decal. Complete product registration card and mail to Fabtech in order to receive future safety and technical bulletins on this suspension.

Vehicles that will receive oversized tires should check ball joints, uniballs and all steering components every 2500-5000 miles for wear and replace as required.

**RE-TORQUE ALL NUTS, BOLTS AND LUGS
AFTER 50 MILES AND PERIODICALLY
THEREAFTER.**

