



Have fun in your garage!®

Safety Data Sheet  
**Glass Sealant**

**SECTION 1: PRODUCT AND COMPANY INFORMATION**

**Product Identifiers**

Name Glass Sealant  
Number 11033, 99634  
Brand Griot's Garage  
Product Use Water seal for automotive glass.

**Supplier**

Name  
Address

Telephone

**Emergency Phone**

Prepared/Revised

**SECTION 2: HAZARD IDENTIFICATION**

**Classification of the substance or mixture**

Physical Hazard Flammable Liquids (Category 3), Flammable liquid and vapor.  
Skin Corrosion / Irritation (Category 2), Causes skin irritation.  
Eye Damage / Irritation (Category 2A), Causes serious eye irritation.  
Specific Target Organ Toxicity (Single Exposure) (Category 3), May cause drowsiness or dizziness.

Environmental Hazards Not classified.

**GHS Label elements and precautionary statements**

Pictogram Flame – Exclamation Mark



Signal word

Prevention

**WARNING**

Keep away from heat, sparks, open flames and hot surfaces. No smoking. Wash thoroughly after handling. Avoid breathing dust/gas/fume/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash it before reuse.

Response

In case of fire: Use dry chemical, foam or water fog to extinguish. Do not use direct water stream.  
IF ON SKIN: Wash with plenty of water. If skin irritation persists: Get medical advice/ attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor/ Seek immediate medical attention if you feel unwell. Specific treatment: See Section 4: First Aid Measures.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage

Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with applicable regulations.

**Hazards not otherwise classified not covered by GHS.**

HMIS Rating: Health hazard: 2 Chronic Health Hazard: 0 Flammability: 2 Physical Hazard 0  
NFPA Rating: Health hazard: 2 Fire Hazard: 2 Reactivity Hazard: 0

**Supplemental Information**

See Section 16 for alphanumeric H-Statements and P-Statements.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS	EC	% Wt.
Isopropyl Alcohol	67-63-0	200-661-7	60-80
Distillates (Petroleum), Hydrotreated Light	64742-47-8	920-901-0	<15

This composition consists of a combination of ingredients. The ones potentially contributing to classified hazards are reported above. The above chemistries are provided for industrial hygiene and environmental purposes and are not intended to represent product specifications.

**SECTION 4: FIRST AID MEASURES**

**Description of first aid measures**

General advice Move out of dangerous area. Consult a physician if you feel unwell. Show this safety data sheet to the doctor and first responders.

In case of eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/ attention.

In case of skin contact Wash with plenty of water. Take off all contaminated clothing and shoes. Wash contaminated clothing before reuse. Decontaminate or discard shoes. Seek immediate medical attention if you feel unwell.

If inhaled Remove person to fresh air and keep comfortable for breathing. Contact a poison center/doctor/seek immediate medical attention if you feel unwell.

If swallowed Rinse mouth. Call a poison center/doctor. Seek immediate medical attention if you feel unwell.

**Most important symptoms and effects, both acute and delayed:** See Sections 2 and 11.

**Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

## Safety Data Sheet: Glass Sealant

### SECTION 5: FIREFIGHTING MEASURES

#### Extinguishing Media

Suitable Use dry chemical, CO<sub>2</sub>, water spray (FOG) or foam.  
Unsuitable Avoid solid water stream as it may scatter and spread fire.  
Special hazards arising from the substance or mixture

Use water spray to cool fire exposed container surfaces and to protect personnel. Thermal decomposition can produce carbon monoxide (highly toxic) and carbon dioxide (an asphyxiant at sufficient concentrations).  
**Advice for firefighters** As in any fire, fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. (MSHA/NIOSH approved or equivalent).

**Further information** If employees are expected to fight fires, training and equipment information can be found in OSHA Fire Brigades Standard (29 CFR 1910.156).

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Use appropriate safety equipment. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. For large spills, warn public of downwind explosion hazard.

#### Environmental precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

#### Methods and materials for containment and cleaning up

Contain spilled material if possible. Collect in suitable and properly labeled containers.

#### Reference to other sections-resources

For additional information, refer to Section 8: Exposure Controls and Personal Protection, Section 7: Handling, Section 12: Ecological Information, Section 13: Disposal Considerations and OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120).

### SECTION 7: HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of dust for dry products and vapor or mist for liquids. When product is flammable or combustible, keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. For precautions see Section 2.

#### Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Specific end use See Section 1.

### SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

#### Control parameters

Under normal conditions of use, no special precautions or control measures are required. If inhalation or skin and eye contact are possible, exposure limits determined by OSHA, ACGIH and NIOSH for components are provided. Limits are for air levels only. Skin contact can cause over exposure even when limits are met.

#### Component Exposure Limits

Isopropanol (67-63-0): Isopropanol (67-63-0): OSHA: The legal airborne permissible exposure limit (PEL) is 400 ppm averaged over an 8-hour work shift. NIOSH: The recommended airborne exposure limit (REL) is 400 ppm averaged over a 10-hour work shift and 500 ppm, not to be exceeded during any 15-minute work period. ACGIH: The threshold limit value (TLV) is 200 ppm averaged over an 8-hour work shift and 400 ppm as a STEL.

Distillates (Petroleum), Hydrotreated Light (64742-47-8): The following exposure limits are for Mineral Oil mist: OSHA: The legal airborne permissible exposure limit (PEL) is 5 mg/m<sup>3</sup> averaged over an 8-hour workshift. NIOSH: The recommended airborne exposure limit is 5 mg/m<sup>3</sup> averaged over a 10-hour workshift and 10 mg/m<sup>3</sup>, not to be exceeded during any 15-minute work period. ACGIH: The recommended airborne exposure limit is 5 mg/m<sup>3</sup> (as the inhalable fraction) averaged over an 8-hour workshift.

#### Appropriate engineering controls

Where possible, enclose operations and use local exhaust ventilation at the site of chemical release. Maintain airborne levels below exposure limit requirements or guidelines. If local exhaust ventilation or enclosure is not used respirators should be worn. Wear protective work clothing. Facilities storing, packaging or utilizing product should be equipped with an eyewash and a safety shower facility. Wash thoroughly immediately after exposure, before breaks and the end of the work shift. Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards to potentially exposed workers.

#### Personal protective equipment

Safety glasses and chemical resistant gloves are recommended whenever chemicals are handled. Obtain detailed information from OSHA Personal Protective Equipment Standard (29 CFR 1910.132) and equipment suppliers.

#### Eye/face protection

Face shield and, or safety glasses are recommended where misting or splashing is a risk. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Wear protective gloves/protective clothing. Dispose of contaminated gloves after use in accordance with applicable regulations and good practices. Wash and dry hands. Wash contaminated clothing and decontaminate shoes before reuse.

#### Respiratory protection

Use when overexposure potential. Improper use of respirators is dangerous. Respirators should only be used with a written program as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

#### Control of environmental exposure

Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with regulations.

## Safety Data Sheet: Glass Sealant

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State: Liquid  
 Color: Water White  
 Odor: Mild Solvent  
 Boiling Point/Range: Not Determined  
 Flash Point: 115°F (46°C)  
 Auto Ignition Temp: Not Determined  
 Lower Flammability Limit: Not Determined  
 Upper Flammability Limit: Not Determined  
 Vapor Pressure (mm Hg@20°F): <1  
 Vapor Density (Air= 1): >1  
 Freezing Point/Melting Point: 32°F (0°C)  
 Solubility (Water): Soluble  
 Specific Gravity: 0.8  
 Evaporation Rate (Butyl Acetate = 1): Not Determined  
 pH: Not Determined  
 Viscosity: Not Determined  
 Volatility: Not Determined.

#### Other Information

Physical Data is typical values based on material tested, but may vary based on composition. Values should not be accepted as guaranteed for every lot or as specifications for this product.

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity** Does not react under normal conditions of use.  
**Chemical Stability** Stable under normal conditions of use.  
**Stability/Incompatibility Conditions to Avoid** Avoid contact with strong oxidizers.  
**Hazardous Reactions/Decomposition Products** None known.  
 Does not decompose under normal conditions; may produce CO, CO<sub>2</sub>, volatile hydrocarbons and other possibly toxic gases in fire.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects

**Component toxicity** Isopropanol (67-63-0): Acute toxicity: LD50 Oral - Rat - 5,045 mg/kg - LC50 Inhalation - Rat - 8 h - 16000 ppm - LD50 Dermal - Rabbit - 12,800 mg/kg - Skin - Rabbit Result: Mild skin irritation - Eyes Rabbit Result: Eye irritation - 24 h.  
Distillates (Petroleum), Hydrotreated Light (64742-47-8): Acute toxicity LD50 Oral - Rat - male and female - > 5,000 mg/kg - LC50 Inhalation - Rat - male and female - 4 h - > 5 mg/l - LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg  
**Mixture toxicity** Skin corrosion/irritation – Inhalation - Serious eye damage/eye irritation - Respiratory or skin sensitization - Germ cell mutagenicity - Reproductive toxicity - Specific target organ toxicity - single exposure - Specific target organ toxicity - repeated exposure - Aspiration hazard: All no data available. Carcinogenicity: Product/Components not classified as a carcinogen by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).  
**Additional Information** None known.

### SECTION 12: ECOLOGICAL INFORMATION

**Component Ecotoxicity** Isopropanol (67-63-0): Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h - Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h - Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h - EC50 Algae - > 1,000.00 mg/l - 24 h.  
Distillates (Petroleum), Hydrotreated Light (64742-47-8): Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - > 100 mg/l - 96 h - Toxicity to daphnia and other aquatic invertebrates static test LC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h  
**Mixture ecotoxicity** Toxicity to Fish - Persistence and Biodegradability - Bioaccumulative Potential - Mobility in Soil: All no data available.  
**Other adverse effects** None known.

### SECTION 13: DISPOSAL CONSIDERATION

#### Waste treatment methods

**Product** Contact a licensed professional waste disposal service to dispose of this material.  
**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### SECTION 14: TRANSPORT INFORMATION

**For Exempt Shipments** DOT: Consumer Package Exemption §173.150 Exceptions for Class 3 (flammable and combustible liquids)  
**For Non-exempt Shipments** DOT: UN number: UN1993 - Class: 3 Packing group: I - Proper shipping name: Flammable Liquid n.o.s. (Isopropanol - Petroleum Distillates) - Reportable Quantity (RQ): 100 lbs.  
 IMDG: UN number: UN1993 - Class: 3 Packing group: I - Proper shipping name: Flammable Liquid n.o.s. (Isopropanol - Petroleum Distillates)  
 IATA: UN number: UN1993 - Class: 3 Packing group: I - Proper shipping name: Flammable Liquid n.o.s. (Isopropanol - Petroleum Distillates) - Reportable Quantity (RQ): 100 lbs.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through a shipper authorized sales or customer service representative.

## Safety Data Sheet: Glass Sealant

### SECTION 15: REGULATORY INFORMATION

Federal	<p><u>TSCA</u>: Components of this product are listed on the TSCA Inventory.</p> <p><u>RCRA</u>: None of the ingredients are currently listed as a substance or a source waste under current regulations (40 CFR 261.31, 32 and 33).</p> <p><u>CERCLA</u>: Contains 75% by weight of Isopropanol (67-63-0) which is listed in table 302.4 of 40 CFR 302 as a hazardous substance with reportable quantity (RQ) of 1000 lbs. Releases to air, land or water which exceed RQ must be reported to the National Response Center, 800-424-8802.</p> <p><u>SARA TITLE III</u>: (Superfund Amendments and Reauthorization Act)</p> <p>302 Components: None are subject to the reporting requirements of Section 302.</p> <p>313 Components: Isopropanol (67-63-0): Subject to reporting levels established by Section 313. Reporting threshold for manufacturing and processing: 25,000 lbs., for other users: 1,000 lbs.</p> <p>311/312 Hazards: Acute Health</p>
States	<p><u>Right to Know Components</u>: MA, PA, NJ &amp; RI: Isopropyl alcohol (67-63-0) – PA &amp; NJ: Distillates (Petroleum), Hydrotreated Light (64742-47-8)</p>
Canada	<p><u>DSL</u>: Components of this product are listed on the Canadian Domestic Substances List.</p> <p><u>WHMIS</u>: Isopropyl alcohol: B2 Flammable Liquid - D2B - Toxic Material Causing Other Toxic Effects (eye irritation in animals) - Uncontrolled product per WHMIS classification criteria.</p>

### SECTION 16: OTHER INFORMATION

Alphanumeric H-Statements and P-Statements.	<p>H226 Flammable liquid and vapor</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P261: Avoid breathing dust/gas/fume/mist/vapors/spray.</p> <p>P264 Wash skin thoroughly after handling.</p> <p>P271: Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304-P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Immediately call a POISON CENTER/doctor/ Seek immediate medical attention if you feel unwell</p> <p>P321 Specific treatment: See Section 4: First Aid Measures.</p> <p>P332 + P313 If skin irritation persists: Get medical advice/ attention.</p> <p>P337 + P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+364 Take-off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use dry chemical, foam or water fog to extinguish. Do not use direct water stream. P403 Store in a well-ventilated place.</p> <p>P403 + P233: Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405: Store locked up.</p> <p>P501: Dispose of contents/container in accordance with applicable regulations.</p>
Disclaimer	<p>The data presented here relates only to the specific material designated herein and does not relate to use in combination with any other materials or in any process. The information set forth above is based on technical data believed to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, no warranties, expressed or implied are made, and no liability is assumed in connection with any use of this information. Judgments as to the suitability of this information for the user's purposes are necessarily the user's responsibility. Although reasonable care has been taken in the preparation of this information, no responsibility is assumed as to the accuracy or suitability of this information for its application to the users intended purpose or for consequences of its use.</p>
Potential Health Effects	<p>This product is a mixture for which no specific health hazard data exists. OSHA requires that one should assume such mixtures present the same health hazards as do any components present in amounts greater than 1% (0.1% for carcinogens). Consumers accessing our SDS information should keep in mind the information is presented in a format required by the U.S. Government's Occupational Safety and Health Administration (OSHA). We provide SDS as a service for our business customers. These industrial SDSs are not applicable to consumer use of these products. We thoroughly evaluate the safety aspects of all of our consumer products prior to their use in the home.</p>