

Tools Required

- Heavy-duty scissors or utility knife
- Poster board or butcher paper
- Pre-paint cleaner, isopropyl alcohol or other non-residue cleaner
- 3M Super Trim Adhesive or other spray trim adhesive (optional)



Installation Tips

Always wear safety glasses, dust mask and gloves when working with HP Stealth Shield™

Use poster board or butcher paper to make a template. For surfaces with severe bends, it may be necessary to cut relief lines or wedges to get product to conform. Transfer template to HP Stealth Shield™ and cut.

All sound insulation should be installed before using the HP Stealth Shield™

Installation Steps

1. Install db Armor™, db Skin™, db Suppressor™ or other manufacturers sound insulation first. Any sound insulation must go on the panel first to maximize its sound insulation capabilities.
2. Use the poster board or heavy paper to make a template. Transfer template to stealth shield and pre-fit HP Stealth Shield to floor or desired body panel
3. Make and cuts and modifications to the HP Stealth Shield now.
4. If you are installing under carpet, lay stealth shield on top of sound insulation, skip to Step 6.
5. *FOR HEADLINERS AND VERTICAL SURFACES ONLY.* Use 3M Super Trim or Super 77 Adhesive. After HP Stealth Shield has been pre-fit and cut, spray back of cloth and panel or component you are applying Stealth Shield to.
6. Allow adhesive to get tacky and press Stealth Shield into place. Start on one edge of panel or component and work out slowly to ensure no “bubbles” occur. Air bubbles will cause the material to not stick and fall off. Press firmly for 30 seconds.
7. Install carpet, headliner, or other interior trim pieces.
8. Cruise cooler!

You may also be interested in

MUFFLER ARMOR™

- Reduces radiant heat up to 70%
- May be cleaned after installation
- Water- and chemical-resistant
- 0.003-inch-thick armor layer
- Includes Thermal-Ties™ for installation

