



# JLT PERFORMANCE™

## JLT 3.0 Oil Separator (2011-2019 Dodge Durango 5.7 Hemi, 2011-2019 Jeep Grand Cherokee 5.7 Passenger Side) #3066P Installation Instructions

Please review complete instructions prior to installing.

Step#	
1	<b>Verify you have all of the following parts included in the kit:</b> (1) JLT Oil Separator w/Hoses, (1) mounting bracket, (2) fine thread machine screws
2	<b>Gather all of the following tools needed for the installation:</b> 15mm socket and ratchet(longer the better), Phillips screw driver
3	Remove engine cover by pulling straight up on the front.
4	<p>Remove plastic portion of the PCV line that runs from rear of engine to the front. The plastic hose is installed into two rubber ends. You may need to use pliers to loosen rubber on plastic hose. Remove the rubber 90 degree coupler from the intake manifold and flip it(install short side onto manifold)</p> 
5	<p>Find the 15mm bolt on the top of the alternator, remove it and install JLT Mounting bracket using same bolt and retighten.</p> 

Take the JLT Oil separator and start to feed the hoses under the large wiring harness while getting the can into place under the bracket. One in place use two supplied mounting screws to mount can to bracket.

You will want the longer hose to be on top of the shorter hose in the routing



6

Reinstall engine cover, to reseal the rubber grommets you may need to give it a good "pop" with your hand to fully seat it.

7

