
PRODUCT INFORMATION

Description	12-24V DOT/ECE LED RHT High & Low Beam Headlights with Turn Signal, FP & DRL - 2 Light Kit
Height	173.00 mm / 6.81 in
Width	144.00 mm / 5.67 in
Depth	86.00 mm / 3.39 in
Shape	Round
Outer Lens Material	Polycarbonate
Outer Lens Color	Clear Clear
Housing Material	Aluminum
Housing Color	Black
Mounting Type	Pedestal
Minimum Operating Temperature	-34 °C / -29.2 °F
Maximum Operating Temperature	49 °C / 120.2 °F
Connector or Wiring	Integral Connector in Housing simulating Delphi 12124107,
Mating Connector	Delphi 12052848
Product Weight	6.80 lbs / 3.08 kgs
Shipping Weight	5.56 lbs / 2.52 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage	12-24 V
Operating Voltage	10-32 V
Transient Spike Protection	150V Peak @ 1 HZ-100 Pul
White Wire	High Beam
Yellow Wire	Low Beam
Black Wire	Ground
Red Wire	Front Position
Purple Wire	DRL
Orange/white Wire	Front Turn
Current Draw	3.67A @ 12V (High Beam) 1.83A @ 24V (High Beam) 2.5A @ 12V (Low Beam) 1.25A @ 24V (Low Beam) .67A @ 12V (DRL) .34A @ 24V (DRL) .83A @ 12V (Front Turn) .42A @ 24V (Front Turn) .08A @ 12V (Front Position) .042A @ 24V (Front Position) .08A @ 12V (Side Marker) .042A @ 24V (Side Marker)




REGULATORY STANDARDS COMPLIANCE



Buy America Standards ECE Reg 6 ECE Reg 87 FMVSS 108 Table VI FMVSS 108 Table XIX IEC IP67 SAE J2087 ECE Reg 112 ECE Reg 7 Eco Friendly FMVSS 108 Table X FMVSS 108 Table XVIII SAE J1395 SAE J222

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output	2,925 (High Beam); 2,025 (Low Beam)
Effective Lumen Output	1,000 (High Beam); 630 (Low Beam)
Nominal LED Color Temperature	5000 K
Beam Pattern(s)	Forward Lighting - Daytime Running Light Forward Lighting - High Beam (DOT/ECE) Forward Lighting - Low Beam (ECE Right Hand) Signalization - Front Position Signalization - Marker Signalization - Turn (Front)





APPLICATIONS



RELATED PRODUCTS



<u>Part Number</u> 0551561

12-24V DOT/ECE LED RHT Right Hand High & Low Beam Headlight with Turn Signal, FP & DRL



Part Number 0551571 12-24V DOT/ECE LED

RHT Left Hand High & Low Beam Headlight with Turn Signal, FP & DRL



Part Number 0551973 12-24V ECE LED LHT

High & Low Beam Headlights with Turn Signal, FP & DRL - 2 Light Kit



Part Number 0551991 12-24V ECE LED LHT Right Hand High & Low Beam Headlight with

Turn Signal, FP & DRL



Part Number 0552001 12-24V ECE LED LHT Left Hand High & Low Beam Headlight with Turn Signal, FP & DRL

