



KC HiLITES

6" GRAVITY LED Inserts





6" GRAVITY LED Inserts 20 Watt

FEATURES


Two Models Available:

- **SAE/ECE CERTIFIED STREET LEGAL** Gravity LED Driving Beam Insert – #42054:
Each Light Rated at: 20-Watt; 2,104 Lumens; 1,310 LUX @ 10 Meters; 131,000 Candela
- Gravity LED Spot Beam Insert – #42134:
Each Light Rated at: 20-Watt; 2,104 Lumens; 2,150 LUX @ 10 Meters; 215,000 Candela
- KC's Gravity Reflective Diode Technology for a More Controlled and Far Reaching Beam Pattern
- Cree XM-L2 T6 LEDs
- 5,000K Color Temperature
- IP68 Rated Sealed Aluminum Housings
- Fits all 6" Halogen KC Daylighter® and Pro-Sport Housings
- Operates on 9 to 32 Volts
- Protected Against EMI Interference

PHOTOMETRICS



PERFORMANCE



DIMENSIONS



KC 6" Gravity LED Inserts

Pair Pack	Single Light									
Part #	Part #	Model / Description	Beam Pattern	Watts	Volts	Lumens	Width	Height	Depth	
42054	42053	6" Gravity LED Insert	Driving - Clear	20	9 - 32	2,104	5.66"	5.66"	3.32"	
42134	42133	6" Gravity LED Insert	Spot - Clear	20	9 - 32	2,104	5.66"	5.66"	3.32"	



KC HiLITES

GRAVITY® LED G6 Optical Inserts



GRAVITY® LED G6 Optical Inserts

**20
Watt**

FEATURES

Three Models Available:

- **SAE J581 & ECE-R112 CERTIFIED STREET LEGAL**
Gravity® LED G6 Optical Insert Driving Beam– #42054:
Each Light Rated at: 20-Watt; 2,300 Lumens;
1,310 LUX @ 10 Meters; 131,000 Candela; Beam
Distance - 724M
- Gravity® LED G6 Spot Beam Insert – #42134:
Each Light Rated at: 20-Watt; 2,300 Lumens;
2,150 LUX @ 10 Meters; 215,000 Candela; Beam
Distance - 927M
- Gravity® LED G6 Wide-40 Beam Insert – #42056:
Each Light Rated at: 20-Watt; 2,300 Lumens;
390 LUX @ 10 Meters; 39,000 Candela; Beam
Distance - 395M
- Patented Gravity® Reflective Diode (GRD) technology
yields more controlled and farther reaching light beams
- 2 x Cree LEDs each light
- 5,000K Color Temperature
- IP 68 Rated, Fully self contained and sealed LED light
housing
- Fits all 6" Halogen KC Daylighter® and Pro-Sport
Housings
- Protected Against EMI Interference
- Backed by our 23 - Year Warranty



KC Gravity® LED G6 Optical Inserts


Pair Pack Part #	Single Light Part #	Model / Description	Beam Pattern	Beam Distance (m)	Watts	Volts	Lumens	Width	Height	Depth
42054	42053	Gravity LED G6 Optical Insert	Driving - Clear	724	20	9 - 32	2,300	5.66"	5.66"	3.32"
42134	42133	Gravity LED G6 Optical Insert	Spot - Clear	927	20	9 - 32	2,300	5.66"	5.66"	3.32"
42056	42055	Gravity LED G6 Optical Insert	Wide-40 - Clear	395	20	9 - 32	2,300	5.66"	5.66"	3.32"



PHOTOMETRICS

Total beam distance with 0.25 LUX - 927m


SPOT BEAM PATTERN



100M 300M 500M 700M

Total beam distance with 0.25 LUX - 724m


DRIVING BEAM PATTERN



150M 300M 450M 600M

Total beam distance with 0.25 LUX - 395m

WIDE-40 BEAM PATTERN



100M 300M 450M 600M

DIMENSIONS

