Double Sides Self-Adjusting Wrench

3616-10 new

- Self-locking function grip, ideal for fastener 8~32mm.
- Anti-slip teeth effective on worn screws.
- Slim jaw allows for working in confined area.
- Multi-purpose to all shape of fastener

KT NO.	Size mm	<u>T</u> a <u>T</u>	@/ @
3616-10	8~17 14~32	466	6 / 36




Adjustable Hook Spanner Wrench

3641

- The joint is equipped with a spring washer to ensure smooth and reliable operation
- Chrome vanadium alloy steel

Capacity mm	L	<u>TaT</u>	8/9
13-35	174	96	12 / 144
35-50	212	166	12 / 108
50-80	285	352	10 / 60
80-120	348	652	5 / 30
120-180	480	1260	4 / 16
	mm 13-35 35-50 50-80 80-120	mm 13-35 174 35-50 212 50-80 285 80-120 348	mm





Chain Wrench

3204



KT NO.	Overall inch	length mm	Capacity(M) mm	₽ġŢ	
3204	8-3/4	225	Ø 60~140	359	50

Strap Wrench


3203




Overall inch	length mm	Capacity(M) mm	₹ a ¶	
8-3/4	223	Ø 60~140	242	50
	Stro	ıp	46	80
8-3/4	223	Ø 60~260	300	50
	Stro	ıp	73	80
	inch 8-3/4	8-3/4 223 Strc 8-3/4 223	8-3/4 223 Ø 60~140 Strap	inch mm mm ### 8-3/4 223 Ø 60~140 242 Strap 46 8-3/4 223 Ø 60~260 300

320670

- Aluminum alloy handle and strong nylon strap for tight grip
- Suitable for oil filter or any polished pipe



KT NO.	Overal inch	l Length mm	Capacity mm	<u> Ta</u> Ţ		
320670	12	295	Ø 60~180	343.8	50	
320600		Nylon strap			50	



Serrated makes

grip tightiy