

INSTALLATION INSTRUCTIONS Part Number: VF2047

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/100,000 mile limited warranty.

When applicable, refer to owner's manual for manufactures installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

- 1. Open glove box. Fig. 1
- 2. Locate your cabin air filter housing by removing back plate or by pressing the 2 knobs to gain access to the cabin air filter housing. NOTE: Some applications will have 6 screws that will need to be removed to drop glove box for access to cabin air filter housing. Fig. 2, 3 & 4
- 3. Remove the cabin air filter housing cover and remove the cabin filter. Fig. 5 & 6
- 4. Once dirty cabin filter is removed clean any debris that might be present in the cabin filter housing.
- 5. Install K&N® Cabin Filter in cabin filter housing making sure that the pull tab is in front (helps for removal of filter). Fig. 7
- 6. Reinstall cabin filter housing cover. With the Cabin Filter installed apply the K&N® Stop Decal. The decal will help notify others that this is a re-usable cabin filter.
- 7. Reverse steps 1 and 2 to complete cabin filter installation.



Fig. 1



Fig. 2



Fig. 3




Fig. 4



Fig. 5



Fig. 6



Fig. 7