Safety Data Sheet (SDS) NANOSKIN IRON FREE



1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name Product identifier Product Family

: NANOSKIN IRON FREE Paint, Wheel & Glass Decontamination/ Fallout Remover

duct identifier : NA-IFE

Product Family : Aqueous mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses : Automotive body detailing

:

1.3 Details of the supplier of the safety data sheet

Company

NANOSKIN Car Care Products Total Import Solutions, Inc.

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910(OSHA HCS)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary Statements

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear eye protection.

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

2.2 GHS Label elements, including precautionary statements SIGNAL WORD: WARNING

Pictogram



3. COMPOSITION/INFORMATION ON INGREDEINTS

Component	CAS number	Warnings	Concentration
Xanthan Gum	11138-66-2		<1%
ALKYL C10-16 ETHER SULFATE SODIUM SALT	68585-34-2		1-5%
Glycerine	56-81-5		>1%
Sodium Xylene Sulfonate	1300-72-7	Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; H315, H319, H335	5-10%
Diethylene Glycol Monobutyl Ether	112-34-5		1-5%
Tetrasodium EDTA	64 -0 2 - 8		1-5%
Sodium Thioglycolate	367-51-1		15-20%

4. FIRST AID MEASURES

First aid procedures

After inhalation:

Get victim to fresh air. Give artificial respiration or oxygen if breathing has stopped. Get

prompt medical attention. Do not give fluids if victim is unconscious. If victim is conscious, rinse mouth with water and contact emergency number listed in section 1.4.

After contact with skin:

Immediately wash skin with soap and water. May cause irritation. Seek medical attention if irritation or allergic reaction is present.

After contact with eyes:

Immediately flush eyes with running water for at least 15 minutes, occasionally lifting the

upper and lower eyelids. Seek prompt medical attention if redness or irritation occurs. Avoid agitation. Abrasives present in substance may scratch eyes. Remove contact lenses if able.

After ingestion:

Rinse mouth with water, contact poison control center or emergency number listed in section 1.4. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES					
Flashpoint: Unknown, aqueus mixture.					
Lower explosion limit: Not applicable					
Upper explosion limit: Not					
Self ignition: Not applicable					
Ignition temperature: not te					
Hazardous combustion products: carbon oxides, sodium oxides, sulfur oxides					
Extinguishing media: water spray jet, alcohol-resistant foam, carbon dioxide, dry powder.					
Special fire fighting procedure: Apply alcohol-type or all purpose-type foams by manufacturers' recommended techniques for large fires or water spray. Use carbon dioxide or dry chemical media for small fires. Use self-					
contained breathing apparatus and protective equipment. Cool endangered containers with water jet.					
Unusual fire and explosion hazards: Product can potentially float on water.					
6. ACCIDENTAL RELEASE MEAS	SURES				
Personal Precautions	Use the Personal protective Equipment recommended in Section 8 of this SDS				
Environmental Precaut	ions Spilled product may present a slipping hazard or result in unintended				
	fumes. Please absorb excess, rinse area and ensure adequate ventilation.				
Methods for Containments					
and Clean-up	Contain large spills as best as possible. Dam flow with appropriate materials and				
	absorb centralized spillage with inert material such as vermiculite, cat litter or				
	diamaceous earth. Sweep and dispose of as needed. For small spills, wipe away				
	and wash exposed area.				
7. HANDLING AND STORAGE					
Handling	Wear gloves while in use, protect hands, face and skin from prolonged and				
repe	eated exposure. May cause skin cracking, drying and irritation.				
Storage	Store with caution. Do not store in temperatures above 120F. Bottle/container				
may	swell and or damage product.				
8. EXPOSURE CONTROLS/PERS					
Exposure Guideline Comments	•				
2-(2- Butoxyethoxy)ethan of 112	-34-5 TWA 10.000000 ppm USA. ACGIH Threshold Limit Values (TLV)				
Engineering Controls	Adequate ventilation necessary.				
Personal Protective Equipment					
Eye/Face Protection	Wear goggles if deemed necessary. Concentrated and diluted solution may				
	ate eyes.				
Skin Protection	Wear gloves while in use.				
Respiratory Protection	Niosh approved respirator for airborne particles if adequate ventilation not				
• •					
General Hygiene Considerations	sent. s Treat products as sum of its components. Wash hands before and after use				
	before smoking eating or drinking.				
and	before smoking eating of drinking.				
9. PHYSICAL AND CHEMICAL PROPERTIES					
Physical State	liquid				
Appearance	yellow				
Particle Size	liquid				
Odor	fragrant				
Odor Threshold	No Available Data				
Molecular Formula	Mixture				
	THACKIC .				

Molecular Weight	Mixture
Boiling Point	200f
Decomposition Temperature	No Available Data
Melting point	32F
Freezing Point	32F
Relative Density	1 g/cm3
Bulk Density	No Available Data
Solubility in Water	100%
Solubility in other liquids	No Available Data
рН	7-7.5
Flash point	No Available Data

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Conditions to Avoid	Avoid extreme temperatures.
Hazardous Decomposition	
Products	carbon oxides, sodium oxides, sulfur oxides
Possibility of Hazardous	
Reactions	Do not bring into contact with oxidizers.

11. TOXICOLOGICAL INFORMATION

ALKYL C10-16 ETHER SULFATE SODIUM SALT

Dermal Acute > 2000 mg/kg LD50 Rat Oral > 2000 mg/kg

TETRASODIUM EDTA

LD50 Oral - rat - 630 - 1,260 mg/kg

DIETHYLENE GLYCOL BUTYL ETHER

LD50 Oral - Rat - male - 7,291 mg/kg (OECD Test Guideline 401) Inhalation: No data available LD50 Dermal - Rabbit - male - 2,764 mg/kg (OECD Test Guideline 402)

SODIUM XYLENE SULFONATE

LD50 Oral - rat - male and female - >= 7,200 mg/kg Inhalation: no data available LD50 Dermal - rabbit - male and female - > 2,000 mg/kg

Skin Irritation/Corrosion

May be irritating to skin.

Eye Irritation/Corrosion

May cause eye irritation/damage.

Effects of Short-Term (Acute) Exposure

No data available.

Inhalation

No data available.

Ingestion

No data available.

12. ECOLOGICAL TOXICITY

General Comments

ALL SURFACTANTS CONTAINED WITHIN THIS FORMULA ARE CLASSIFIED AS READILY BIODEGRADABLE.

ALKYL C10-16 ETHER SULFATE SODIUM SALT

Acute Fish LC50 Fish 2.3 mg/l, 96 hours Aquatic Crustacea EC50 Water flea (Ceriodaphnia dubia) 2.33 - 4.81 mg/l, 48 hours

ETHYLENE GLYCOL MONOBUTYL ETHER

Toxicity to fish static test LC50 - Lepomis macrochirus - 1,300 mg/l - 96 h (OECD Test Guideline 203) Toxicity to daphnia and other aquatic invertebrates static

test EC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h (Directive 67/548/EEC, Annex V, C.2.) Toxicity to algae static test EC50 - Desmodesmus subspicatus (Scenedesmus subspicatus) - > 100 mg/l - 96 h (OECD Test Guideline 201) Toxicity to bacteria LC50 - Pseudomonas putida - 1,170 mg/l - 16 h

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, provincial and local government regulations. Containers should NOT be reused. Containers should be disposed of in accordance with government guidelines.

14. TRANSPORT INFORMATION

Shipping Information

Product is not UN rated. Product is not flammable or known to have any restrictions in transport. Ensure, before use, that product is not restricted by any local, state or federal environmental restrictions not otherwise stated.

Special Shipping Information

Not applicable. NFPA/HMIS 1 HEALTH **0 FLAMMABILITY 0 REACTIVITY**

15. REGULATORY INFORMATION

Massachusetts Right To Know Components

Pennsylvania Right To Know Components

Sodium xylenesulphonate CAS-No. 1300-72-7 Revision Date

Ethylenediaminetetraacetic acid tetrasodium salt dihydrate CAS-No. 10378-23-1 Revision Date

2-(2-Butoxyethoxy)ethanol CAS-No. 112-34-5 Revision Date 1989-08-11

New Jersey Right To Know Components

2-(2-Butoxyethoxy)ethanol CAS-No. 112-34-5 Revision Date 1989-08-11

Sodium xylenesulphonate CAS-No. 1300-72-7 Revision Date

Ethylenediaminetetraacetic acid tetrasodium salt dihydrate CAS-No. 10378-23-1 Revision Date

California

Product is not known, at this time, to contain any California prop 65 materials.

16. OTHER INFORMATION

Total Import Solutions, Inc. dba NANOSKIN Car Care Products

SDS Prepared by Disclaimer This health and safety information is correct to the best of our knowledge and belief at the date of its publication, but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, to maintain revised copies of this information to be requested. When applicable, revised copies shall be sent to customers whom have been directly supplied with this substance. It must be known that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the user. The information given in the Data Sheet is designed only as guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only be competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this sheet.