



PART NUMBER

Norton Quick-Set Seam Sealer

076607**82750**

PACKAGE SIZE

10.1 fl. oz. Cartridge

DESCRIPTION

Quick-Set Seam Sealer can be used to seal any body seam against moisture or dust and to finish skin panels. Applies easily, skins in 2 minutes, paintable in 30. Outstanding toolability. Remains flexible when dry. Excellent adhesion to numerous substrates.

APPLICATION

1. Clean surface with Norton Panel and Adhesive Cleaner (076607**82780**)
2. Sand with 80 grit
3. Cut nozzle to desired bead size
4. Apply Norton Quick-Set Seam Sealer
5. Remove excess material with Norton Panel and Adhesive Cleaner (076607**82780**)
6. Material can be painted over in 30 minutes under normal conditions

SUBSTRATES

Bare Steel, Bare Galvanized, Bare Aluminum, Primer- Self-Etch, 1K, 2K

TECHNICAL DATA

PAINT TIME: 30 minutes minimum (check for compatibility)
 MIXING: Ready to Use
 APPEARANCE: Beige
 SHELF LIFE: 1 Year

REGULATORY

CATEGORY: SEALANT			
VOC Content	<3.50 lb/gal (420 g/l)	Weight % of Exempt Compounds	0
Weight % Volatiles	35% w/w maximum	Volume % of Exempt Compounds	0
Weight % of Water	0	Density of Material #/gal	9.6 to 10.0 lb/gal

PRECAUTIONS

For professional use only. Before use, read and follow all TDS, label and SDS precautions.



FORM # 8743-82750 REV. 08/19
 © Saint-Gobain August 2019.
 Norton is a registered trademark of Saint-Gobain Abrasives.