

DID YOU KNOW THERE ARE OVER 3 MILLION VEHICLES ON THE ROAD

THAT MAY REQUIRE DPF SERVICE IN THE NEXT 12 MONTHS?



5280 DIESEL PARTICULATE FILTER CLEANER

- Patented Process
- PTEN Innovation Award 2010

The Diesel Particulate Filter (DPF) Cleaner was designed with shop service in mind. The patentedcleaning process allows the DPF to be cleaned as part of a general maintenance schedule at the service location with minimal time away

from the vehicle. Its portability allows the unit to be placed as close to the vehicle as possible and to be stored wherever needed in the service facility.



DPF CLEANER FEATURES

- Robust design For long shop life. Can be used as part of a preventative maintenance program.
- Patented High Pressure cleaning process for thorough cleaning of ash from DPF – produces 10 times the burst energy of competitive low pressure units.
- Initial Burst Quick check To identify filters too plugged for proper cleaning.
- Movable with locking wheels For placement throughout the shop.
- Computer Controlled Process Based on OE Requirements for "Start to End" cleaning without constant technician monitoring.
- Containment of hazardous ash For easy disposal.
- HEPA Filter Air Exhaust System To exceed environmental air standards for shop.
- Operates on standard 115V outlet.
- Proven to clean to over 92% efficiency. (3)

(3) Third-party OEM test results using pin gauge measurement with approved Bosch adapters and burst cycles. Actual results may vary.









DPF CLEANER PART NUMBERS

No. 5280 OTC Diesel Particulate Filter (DPF) Cleaner

Includes the following items:

 No. 535936
 Small Cone

 No. 543887
 Medium Cone

 No. 543885
 Large Cone

 No. 553913
 CAT Adapters

 No. 553915
 Cummins Adapters





No. 556889 Detroit Diesel Upgrade Kit

No. 553990 UD TRUCK (with Hino Engine) Upgrade Kit

No. 553991 Isuzu Upgrade Kit
No. 553993 Volvo/Mack Upgrade Kit
No. 558181 Navistar Upgrade Kit *

* Requires use of 5281 DPF Thermal Processing Unit.



J-47399 HORIZONTAL DPF HANDLER

- The Universal mounting assembly adjusts, front to back and side to side for easy DPF handling
- The height range of 6-1/2" to 29-1/2" is ideal for most of today's trucks
- Safety strap holds the load securely while moving about the shop
- Size allows for handling of all known DPF's

Specifications:

Overall Length: 34-1/2" Overall Width: 19-3/8"

Max. Height: 29-3/4" Min. Height: 7-1/2"

Side: 30° Tilt Front: 15°

Back: 15°





5281 – OTC DPF THERMAL PROCESSING UNIT

The 5281 DPF Thermal Processing Unit is a device which will thermally regenerate a DPF unit at a controlled, pre-programmed rate.

Sometimes, the DPF cannot be regenerated on the truck due to a failure with the vehicle's own regeneration system, or in the case of retrofit applications, a lack of an on-vehicle regeneration system. Thermal regeneration of DPFs is used in conjunction with the OTC 5280 DPF Cleaner, and maximizes the cleaning efficiency of the cleaner.

Designed to facilitate the cleaning of dirty filters – especially those with high amounts of wet soot, and unburned hydrocarbons.

- Pre-programmed thermal profile controls temperature 'ramp up' and 'cool down' to protect the DPF from thermal shock, reducing the risk of cracking the DPF.
- Includes both standard cycle and "pre-treat" cycle for oil-soaked filters.
- Holds temperature constant for two hours to ensure complete regeneration of filter.
- Built-in electronic safety lock prevents unauthorized opening of the door when temperatures exceed 200 degrees F.
- Large chamber accommodates various DPF sizesand shapes.
 Front access door allows for easy access to the thermal chamber.
- 220VAC / 60Hz / Single phase / 50 Amp.
- 1-year warranty.
- CE, UL201, UL499.
- Internal chamber dimension: 24" (L) x 24" (W) x 26" (H).





Electronic safety lock.