



Operating Instructions
for:


6476
(511543 & 511544)

Ford Camshaft Positioning Tool Set

Application: 1997 – 2002 4.6L Econoline, F-Series Truck (VIN W)
1997 – 2002 5.4L Econoline, Expedition, F-Series Truck
1997 – 2002 6.8L V10 Econoline
1998 – 2002 5.4L Navigator


2-Hole
Camshaft
Sprocket

No. 511543



18 mm
Hex Hd.
Camshaft
Sprocket

No. 511544




No. 511543

1. **Two-hole Camshaft Sprocket:** Use tool No. 511543 to position camshaft sprocket (2-hole) on the engine as shown.

18 mm Hex Hd. Camshaft Sprocket: Use tool No. 511543 with tool No. 511544 to position camshaft sprocket (18 mm hex hd.) on the engine as shown.

2. Service the timing chain as required according to procedures in the vehicle service manual.
3. Torque fasteners to factory specifications.



511543

511544

NOTE:

- 511543 is the same as Ford No. 303-569 (T96T-6256-AR1) and 511544 is the same as Ford No. 303-570 (T96T-6256-AR2).
- This tool is used with No. 6477 (511545) Ford Camshaft Holding Tool.



WARNING: Wear eye protection that meets ANSI Z87.1 and OSHA standards.

