

# **OTC Oil Filter Sockets**

# **Domestic & Import Sockets**

## GM Oil Filter Socket - 74 mm, 15 Flutes

- Works on 1999–2002 Olds Intrigue and 2001–'02 Olds Aurora
- This is a required tool to remove the oil filter cap from the oil pan to access the filter cartridge.

No. 6901 - GM oil filter socket, 74 mm, 15 flutes. Wt., 9 oz.

# Ford / Mazda and Toyota Oil Filter Socket—75.6 mm, 14 Flutes

#### **Ford**

- Designed at 75.6 mm to fit the new 2.3L 4-cylinder engines.
- Works on Ford Fusion, Mercury Milan, Mazda 3, Mazda 5, and Mazda 6.

### Toyota

#### **Avalon**

2005-'07 V6 3.5L (2GR-FE), 1995-2004 V6 3.0L (1MZ-FE)

#### Camry

2007 V6 3.5L (2GR-FE), 2004-'06 V6 3.3L (3MZ-FE), 1994-2006 V6 3.0L (1MZ-FE)

### **Camry Solara**

2004-'07 V6 3.3L (3MZ-FE)

#### Highlander

2004–'07 V6 3.3L (3MZ-FE) — also works on the hybrid version of this engine

2001-'03 V6 3.0L (1MZ-FE)

### RAV4

2006-'07 V6 3.5L (2GR-FE)

### Sienna

2007 V6 3.5L (2GR-FE)

2004-'06 V6 3.3L (3MZ-FE)

1998-2003 V6 3.0L (1MZ-FE)

No. 6903 – Ford / Mazda and Toyota oil filter socket, 75.6 mm, 14 flutes. Wt., 4 oz.

# Hyundai and Kia Oil Filter Socket—88.22 mm, 15 Flutes

- · Works on 2006 Hyundai Sonata and Santa Fe 3.3L V6 engines.
- Works on 2007 Hyundai Azera, Veracruz and Entourage 3.8L V6 engines.
- Works on 2007 Kia Amanti, Sedona and Sorrento 3.8L V6 engines.

No. 6904 – Hyundai and Kia oil filter socket, 88.22 mm, 15 flutes. Wt., 4 oz.

## Subaru Oil Filter Socket-66.5 mm, 14 Flutes

- Socket fits between the exhaust manifold and the oil filter for easy removal and installation of the filter.
- Works on 2003
  –newer Subaru vehicles having the 2.5L 4-cylinder, turbo engine.

No. 6905 - Subaru oil filter socket, 66.5 mm, 14 flutes. Wt., 4 oz.

**07-50** ©2007 SPX Corporation. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Product shipped may differ from photo(s) shown.

