

# **Technical Data Sheet**

# Permatex® Decal & Paint Stripper

#### PRODUCT DESCRIPTION

Permatex® Decal & Paint Stripper is a solvent stripper specifically designed to quickly remove decals, stickers and paint from bumpers and truck bodies.

S.I.N.: 834-300

CAUTION: This product will remove paint. Do not use to remove decals from painted surfaces.

#### **PRODUCT BENEFITS**

- Eliminates time consuming scraping and sanding
- Adheres to vertical surfaces


### **TYPICAL APPLICATIONS**

Removes decals, bumper stickers or paint from:

- Auto bodies
- Bumpers
- Windows
- Windshields

#### **DIRECTIONS FOR USE**

- Provide adequate ventilation and protect painted surfaces.
- Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
- 3. Hold the can 8 to 10 inches from the surface to be stripped. Press the nozzle and discharge and saturate the product liberally on the area to be removed.



4. Allow 5 to 10 minutes for product to penetrate. Then lift the decal with a putty knife.

#### For Cleanup

1. Clean hands with Permatex® brand hand cleaners.

## **PROPERTIES OF MATERIAL**

Chemical Type
Chemical Type
Chlorinated solvent
Appearance
Odor
Odor
Flash Point
Aerosol, contents under pressure,
consult MSDS
NFPA 704 Flammability Rating

Typical Value
Chlorinated solvent
Milky liquid
Aerosol, contents under pressure,
consult MSDS
4 (Highly flammable)

### **GENERAL INFORMATION**

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

#### ORDERING INFORMATION

F	Part Number	Container Size
80	0577 (161DA)	16 oz. aerosol can

#### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8\_ to 28\_C (46\_ to 82\_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

PERMATEX PRODUCTS AUTO DETAILING