



RED LINE 75W90 GL-5 GEAR OIL



- Most popular Red Line gear oil, with thousands of applications for passenger cars, light trucks and racing vehicles
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- This product is not designed for use in most manual transmissions or transaxles in passenger vehicles, since the extreme slipperiness may cause synchronizer mesh issues that lead to shifting problems
- Recommended for API GL-5, GL-6, MT-1, MIL-L-2105E, SAE J2360 and Chrysler spec MS-9763
- Suitable replacement for a differential calling for 80W90 or SAE 90 gear oil.

RECOMMENDED FOR:

API GL-5 and MT-1	Castrol	GM	89021675	Dexron [®] L.S.Gear Oil	Mitsubishi	Mercedes Benz
MIL-L-2105E	SAF-Carbon Mod	1050010	89021676	Tex 9622	3775610	235.0
SAE J2360	SAF-XO	1052271	89021677		8149630	235.20
Chrysler spec MS-9763	SAFX-LS	10950849	89021678	Mazda	MZ320345	235.6
BMW		10953455	92184900	0000-77-80W9-QT	DiaQueen LSD Gear Oil	235.8
83 22 9 407 768	Ford	12345841	9985290	Fuchs	Subaru	A 001 989 17 03-10
83 22 9 407 768	ES-PM-M2013	12345977	9986115	Titan Race Syn 5	SOA635001	A 001 989 27 03-10
83 22 9 407 768	WSP-M2C197-A	12378261	9986115		SOA635048	A 001 989 28 03-10
83 22 9 407 768	WSP-M2C201-A	12378557	9986207	Nissan		A 001 989 58 03-10
83 22 9 407 768	WSS-M2C939-A	88862624	9986290	KLD37-00001P	Toyota	
83 22 9 407 768	XY-75W90-QLS	88862625	9986115		08885-81006	
SAF-XO	XY-75W90-TQL	88901362	9986207			
SAFX-LS	XY-80W90-QL	89021671	9986290			

TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W90
Vis @ 100°C, cSt	16.1
Vis @ 40°C, cSt	112
Viscosity Index	155
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	1100 @-40°C

PACKAGE SIZES:

- 57904 - 75W90 GL-5 Gear Oil - quart
- 57905 - 75W90 GL-5 Gear Oil - 1 gallon
- 57906 - 75W90 GL-5 Gear Oil - 5 gallon
- 57907 - 75W90 GL-5 Gear Oil - 16 gallon
- 57908 - 75W90 GL-5 Gear Oil - 55 gallon

ABOUT RED LINE GEAR OIL FOR DIFFERENTIALS

- Full-synthetic formulas created from polyol ester base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester base stocks and friction modifiers provide additional slipperiness to lower operating temperatures by reducing the sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetics and conventional gear oils
- Exceed API GL-5 specifications
- Engineered to provide the highest degree of protection and improvement of differential efficiency for better mileage, longer drain intervals and less wear