

Installation Specifications

Installation Specifications:

		PINION BEARING PRELOAD			R.G.BOLT	BEARING CAP
	DIFFERENTIAL	NEW	USED	BACKLASH	TORQUE	TORQUE
AAM	MODEL	(Inch Pounds)	(Inch Pounds)	(.001” inch)	(Foot lbs)	(Foot lbs)
	9.25”	15-22	7-9	6-10	75	80
	10.5” (Dodge)	22-28	7-9	6-10	90	90
	11.5”	25-35	7-9	6-10	110	110
AMC						
	MODEL 20	14-19	6-8	6-10	65	65
	MODEL 35	12-15	6-7	6-10	55	55
GM						
	OLDS/PONT D/O	14-19	6-7	6-10	55	60
	55 Chevy	14-18	6-8	6-10	55	60
	7.2” IFS	11-14	6-7	6-10	55	60
	7.5”	12-15	6-7	6-10	65	60
	7.75”	12-15	6-7	6-10	65	60
	8.2”	12-15	6-7	6-10	55	60
	8.25” IFS	14-19	6-8	6-10	65	55
	8.5” & 8.6”	14-19	6-8	6-10	65	60
	9.5” & 9.25”IFS	15-22	7-9	6-10	75	80
	12” PASSENGER	14-19	6-8	6-10	55	60
	12” TRUCK	13-15	6-7	6-10	55	60
	14T 10.5”	20-35	8-11	6-10	120	135
CHRYSLER						
	7.25”	12-14	6-7	6-10	55	50
	8-25”	12-15	6-8	6-10	55	60
	8.75” ’41’	13-15	6-8	6-10	55	90
	8.75” ’42’	15-25	7-10	6-10	55	90
	8.75” ’89’	14-19	6-9	6-10	55	90
	9.25”	14-19	6-9	6-10	65	75
DANA						
	MODEL	(Inch Pounds)	(Inch Pounds)	(.001” inch)	(Foot lbs)	(Foot lbs)
	DANA 28	10-13	5-6	6-10	55	50
	DANA 30	12-15	6-8	6-10	55	55
	DANA 35	12-15	6-7	6-10	55	55
	DANA 44	14-19	6-9	6-10	55	60
	DANA 50	14-19	6-9	6-10	65	60
	DANA 60,61,70U	17-30	8-10	6-10	110	80
	DANA 70 & 70HD	20-35	8-10	6-10	110	80
	DANA 80	25-40	9-11	4-10	175	90
FORD						
	7.5”	14-19	6-8	11-16	60	60
	8.0”	12-14	6-7	10-15	60	60
	8.7”	14-19	6-8	10-15	60	60
	8.8”	14-19	6-8	11-16	60	60
	9” OEM R&P	13-15	6-7	10-16	70	60
	9” NON OEM			7-10		
	9” DAYTONA	14-16	6-8			
	9-3/8”	14-16	6-8	10-15	70	60
	10.25 & 10.5”	20-35	6-8	11-16	95	80
TOYOTA						
	Passenger	11-13	5-6	6-9	55	60
	7.5, 8” 4cyl	12-15	5-6	6-10	65	70
	8” V6, 8” Rev	14-17	5-6	6-10	65	70
	8 clamshell	14-17	5-6	6-9	70	n/a
	8.4” Tacoma	15-18	5-6	6-10	70	70
	9” clamshell	15-22	5-6	6-10	70	n/a
	9.5” LC	12-15	5-6	6-10	70	70
	10.5”	20-25	5-6	6-10	100	100