

DESCRIPTION

SEM Solve is a virgin solvent blend to clean panels prior to refinish or repair.

FEATURES

- Effectively removes adhesive residue, wax, grease, road tar, oil, silicone, paint overspray and bug remnants
- Easy to use
- Leaves no residue

SUITABLE SUBSTRATES

- Bare steel
- Bare aluminum
- Primed or painted surfaces
- SMC & plastic – limit exposure

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
38371	SEM Solve	Clear	Gallon
38373	SEM Solve	Clear	20 oz. Aerosol
38374	SEM Solve	Clear	Quart
38375	SEM Solve	Clear	5 Gallon

VOC Actual (38371, 38374, 38375):	773 g/L
VOC Actual (38373):	712 g/L

Check local VOC regulations to ensure compliance in your area.

HANDLING AND APPLICATION

MIXING:

Ready to use.

APPLICATION:

Apply **SEM Solve** directly to surface or clean cloth. Wipe surface with enough material to adequately float contaminants out of sand scratches. Wipe dry in one direction with a clean, lint-free cloth, turning and changing cloths often. If **SEM Solve** air dries on the surface, re-wet and dry completely with a clean, lint free cloth. Do not leave solvent cloth on painted surface.



Check local VOC regulations to ensure compliance of all products in your area.

Note:

Avoid prolonged contact with SMC, fiberglass and plastic. Do not saturate exposed fibers of SMC and fiberglass.

STORAGE:

SEM Solve should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames.

The shelf life for **38373** is 5 years when stored under normal conditions, while the shelf life for **38371**, **38374** and **38375** is unlimited.