



# RUBBERIZED UNDERCOATING

## TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

### DESCRIPTION

**Rubberized Undercoating** and **Low VOC Rubberized Undercoating** are premium, paintable, textured coatings for sound dampening, chip resistance, rust protection and corrosion protection.

### FEATURES

- Sound-dampening properties
- Chip and corrosion resistant
- Paintable without bleed through
- Fast-drying
- Uniform final appearance
- Aerosol includes straw for tight spots
- Quality asphalt free formula

### SUITABLE SUBSTRATES

- Properly prepped and primed surfaces

### TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39513	Rubberized Undercoating (Europe Only)	White	24 oz. Aerosol
39523	Rubberized Undercoating	Black	24 oz. Aerosol
40523	Low VOC Rubberized Undercoating	Black	24 oz. Aerosol
40524	Low VOC Rubberized Undercoating	Black	Quart

	Regulatory	Actual	EU	%
<b>VOC 39513</b>	588 g/L, 4.90 #/gal	588 g/L, 4.90 #/gal	588 g/L	71%
<b>VOC 39523</b>	572 g/L, 4.77 #/gal	572 g/L, 4.77 #/gal	572 g/L	66%
<b>VOC 40523</b>	468 g/L, 3.90 #/gal	348 g/L, 2.90 #/gal	598 g/L	< 40%
<b>VOC 40524</b>	429 g/L, 3.57 #/gal	318 g/L, 2.65 #/gal	666 g/L	N/A

Paintable: Yes

### HANDLING AND APPLICATION

#### PREPARATION:

1. Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner**. Remove any loose paint, rust, oil and grease.
2. Blow off and clean again with **SEM Solve** or **XXX Universal Surface Cleaner**.



Check local VOC regulations to ensure compliance of all products in your area.

---

## APPLICATION:

### AEROSOL:

---

<b>Distance:</b>	6-8"
<b>Coats:</b>	2-3 medium wet
<b>Flash time:</b>	3-5 minutes
<b>Top Coat time:</b>	30 minutes

---

#### Note:

When utilizing any **Rubberized Undercoating** product over 1K coatings, softening or separation may occur. Test in an inconspicuous area for compatibility.

#### Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.

### BULK:

- 
1. Attach **Low VOC Rubberized Undercoating** to **Economy Coating Gun** or **Premium Undercoat Gun**.
  2. Using 35-40 psi, apply 2-3 medium coats, allowing 3-5 minutes flash time between coats.

#### Note:

When utilizing any **Rubberized Undercoating** product over 1K coatings, softening or separation may occur. Test in an inconspicuous area for compatibility.

#### Note:

Clean gun immediately after use with solvent compliant in your area. Final texture, flash times, and dry times are affected by gun distance, air pressure, temperature, and humidity.

## STORAGE:

**Rubberized Undercoating** and **Low VOC Rubberized Undercoating** should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Rubberized Undercoating** and **Low VOC Rubberized Undercoating** is 3 years when stored under normal conditions.



Check local VOC regulations to ensure compliance of all products in your area.

---

## RELATED PRODUCTS:

<b>Part:</b>	<b>Product Name:</b>	<b>Size:</b>
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
71102	Economy Coating Gun	1 Each
71109	Premium Undercoat Gun	1 Each
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart