Page 1/12 Reviewed on 06/21/2017

Printing date 06/28/2017

1 Identification

· Product identifier

· Trade name: 39977 Panel Vibration Control Material

· Article number: 39977

· Application of the substance / the mixture Sealant

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to organs.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 1)

· Hazard-determining components of labeling:

ALIPHATIC AMINE (PROPRIETARY)

2-piperazin-1-ylethylamine

CASTOR OIL GLYCIDAL ETHER

EPOXY RESIN MODIFIER

bisphenolA(chloro)oxirane polymer

· Hazard statements

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H335 May cause respiratory irritation.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P270Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3Fire = 1



Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
	EPOXY RESIN MODIFIER	13 - 30%
	ALIPHATIC AMINE (PROPRIETARY)	13 - 30%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	10 -13%
	Mercaptan Terminated Polymer NJTS 800938 5952	7 - 10%
140-31-8	2-piperazin-1-ylethylamine	7 - 10%
25068-38-6	bisphenolA(chloro)oxirane polymer	7 - 10%
67762-90-7	FUMED SILICA	5 - 7%
25154-52-3	nonylphenol	5 - 7%
	Amine proprietary	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- $\cdot \textit{After swallowing:} \ Drink \ copious \ amounts \ of \ water \ and \ provide \ fresh \ air. \ Immediately \ call \ a \ doctor.$
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

140-31-8	2-piperazin-1-ylethylamine	6.4 mg/m3
25068-38-6	bisphenolA(chloro)oxirane polymer	90 mg/m3
67762-90-7	FUMED SILICA	120 mg/m ³
25154-52-3	nonylphenol	4.9 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m3
107-21-1	ethanediol	30 ppm
1333-86-4	Carbon black	9 mg/m3
106-89-8	1-chloro-2,3-epoxypropane	1.7 ppm
PAC-2:		
140-31-8	2-piperazin-1-ylethylamine	71 mg/m3
25068-38-6	bisphenolA(chloro)oxirane polymer	990 mg/m3
67762-90-7	FUMED SILICA	1,300 mg/m ²
25154-52-3	nonylphenol	53 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m3
107-21-1	ethanediol	150 ppm
1333-86-4	Carbon black	99 mg/m3
106-89-8	1-chloro-2,3-epoxypropane	24 ppm
<i>PAC-3:</i>		
140-31-8	2-piperazin-1-ylethylamine	420 mg/m3
25068-38-6	bisphenolA(chloro)oxirane polymer	5,900 mg/m ²
67762-90-7	FUMED SILICA	7,900 mg/m ²
25154-52-3	nonylphenol	320 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m3
107-21-1	ethanediol	900 ppm
	Carbon black	590 mg/m3



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

	(Contd. of page 4)
106-89-8 1-chloro-2,3-epoxypropane	72 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

SEM Project of the Second of t

Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical an	d chemical	properties
---------------	------------	------------

· Information on basic phy	sical and chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	According to product specification
. Odor:	Characteristic

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:220 °C

· Flash point: 257 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 315 °C

• Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.
In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapor pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapor density
 Evaporation rate
 1.09529 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.

(Contd. on page 7)



Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 6)

	(Conta. or page o)
· Solvent content: Organic solvents:	0.0 %
Solids content: · Other information	99.6 % No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	· LD/LC50 values that are relevant for classification:		
140-31-	140-31-8 2-piperazin-1-ylethylamine		
Oral	LD50	2140 mg/kg (rat)	
Dermal	LD50	880 mg/kg (rabbit)	
25154-5	25154-52-3 nonylphenol		
Oral	LD50	1620 mg/kg (rat)	

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1333-86-4	Carbon black	2B
106-89-8	1-chloro-2,3-epoxypropane	2A

(Contd. on page 8)

SEM

Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 7)

· NTP (National Toxicology Program)

106-89-8 1-chloro-2,3-epoxypropane

R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	UN1760	
UN proper shipping nameDOTADR	Corrosive liquids, n.o.s. (nonylphenol) 1760 Corrosive liquids, n.o.s. (nonylphenol), ENVIRONMENTALLY HAZARDOUS	
· IMDG, IATA	CORROSIVE LIQUID, N.O.S. (nonylphenol)	

(Contd. on page 9)

SEM

Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 8) · Transport hazard class(es) $\cdot DOT$ 8 Corrosive substances · Class · Label · ADR, IMDG · Class 8 Corrosive substances · Label \cdot IATA 8 Corrosive substances · Class · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: Product contains environmentally hazardous substances: nonylphenol · Marine pollutant: Yes *Symbol* (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special precautions for user Warning: Corrosive substances · EMS Number: F-A, S-B· Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L ORM-D CFR49-173,150,156,306 · Remarks · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 9)

· IMDG	5L
· Limited quantities (LQ)	- -
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1760 CORROSIVE LIQUIDS, N.O.S. (NONYLPHENOL), 8, III,
	ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substances):			
106-89-8 1-	106-89-8 1-chloro-2,3-epoxypropane		
· Section 313	(Specific toxic chemical listings):		
25154-52-3	nonylphenol		
107-21-1	ethanediol		
106-89-8	1-chloro-2,3-epoxypropane		
· TSCA (Toxi	c Substances Control Act):		
74398-71-3	CASTOR OIL GLYCIDAL ETHER		
140-31-8	2-piperazin-1-ylethylamine		
25068-38-6	bisphenolA(chloro)oxirane polymer		
67762-90-7	FUMED SILICA		
25154-52-3	nonylphenol		
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol		
107-21-1	ethanediol		

· Proposition 65

· Chemicals known to cause cancer:	
74398-71-3	CASTOR OIL GLYCIDAL ETHER
25068-38-6	bisphenolA(chloro)oxirane polymer
107-21-1	ethanediol
1333-86-4	Carbon black
106-89-8	1-chloro-2,3-epoxypropane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

1333-86-4 Carbon black

106-89-8 1-chloro-2,3-epoxypropane

· Chemicals known to cause reproductive toxicity for males:

106-89-8 1-chloro-2,3-epoxypropane

· Chemicals known to cause developmental toxicity:

107-21-1 ethanediol

(Contd. on page 11)

Reviewed on 06/21/2017

Printing date 06/28/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 10)

· Cancerogenity categories

· EPA (Env	ironmental Protection Agency)	
106-89-8	B2	
· TLV (Thr	eshold Limit Value established by ACGIH)	
107-21-1	ethanediol	A4
1333-86-4	Carbon black	A4
106-89-8	1-chloro-2,3-epoxypropane	A3
· NIOSH-C	a (National Institute for Occupational Safety and Health)	
1333-86-4	Carbon black	
106-89-8	1-chloro-2,3-epoxypropane	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

ALIPHATIC AMINE (PROPRIETARY)

2-piperazin-1-ylethylamine

CASTOR OIL GLYCIDAL ETHER

EPOXY RESIN MODIFIER

bisphenolA(chloro)oxirane polymer

- · Hazard statements
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H371 May cause damage to organs.
- H335 May cause respiratory irritation.
- · Precautionary statements

D201	α_1 .	. 1	•	1 (
P201	()htain cr	าดดาสโ	instructions	hotore use
1 201	Obluit St	<i>icciai</i>	mon neurons	before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 12)



Printing date 06/28/2017 Reviewed on 06/21/2017

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 11)

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Date of preparation / last revision 06/28/2017 / 7
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation – Category I Skin Sens. 1: Skin sensitisation – Category I

Repr. 2: Reproductive toxicity – Category 2

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

* Data compared to the previous version altered.

USA