

## DESCRIPTION

**Ez Coat** is a direct to metal coating that matches the color and gloss of factory primer and e-coat colors.

## FEATURES

- OEM recommended
- Duplicates factory appearance
- Direct to steel and aluminum
- Quick curing and hiding
- Available in 9 popular OEM colors
- Paintable with most automotive basecoats

## SUITABLE SUBSTRATES

- Bare Metal
- OEM finishes
- Primer

## TYPICAL PROPERTIES

| Part: | Product Name: | Color:      | Container:     |
|-------|---------------|-------------|----------------|
| 62213 | Ez Coat       | Black       | 16 oz. Aerosol |
| 62223 | Ez Coat       | Olive Green | 16 oz. Aerosol |
| 62233 | Ez Coat       | Light Green | 16 oz. Aerosol |
| 62243 | Ez Coat       | Gray        | 16 oz. Aerosol |
| 62253 | Ez Coat       | Tan         | 16 oz. Aerosol |
| 62263 | Ez Coat       | Olive Brown | 16 oz. Aerosol |
| 62273 | Ez Coat       | White       | 16 oz. Aerosol |
| 62283 | Ez Coat       | Field Drab  | 16 oz. Aerosol |
| 62293 | Ez Coat       | Dark Green  | 16 oz. Aerosol |

|                           |   |
|---------------------------|---|
| <b>MIR:</b>               | < 1.5                                   |
| <b>Category:</b>          | EFA                                     |
| <b>Coverage:</b>          | 13 ft <sup>2</sup> per can @ 1 mils DFT |
| <b>Recommended coats:</b> | 2–3 coats                               |
| <b>Top coat time:</b>     | 15 minutes                              |

Check local VOC regulations to ensure compliance of all products in your area.



Check local VOC regulations to ensure compliance of all products in your area.

---

## HANDLING AND APPLICATION

### PREPARATION:

1. Clean surface thoroughly with **SEM Solve** or **XXX Universal Surface Cleaner**.
2. Sand with P320 grit or finer paper and re-clean with **SEM Solve** or **XXX Universal Surface Cleaner**.

### APPLICATION:

|                    |                            |
|--------------------|----------------------------|
| <b>Coats:</b>      | 2–3 medium coats           |
| <b>Flash time:</b> | 5–10 minutes between coats |
| <b>Dry time:</b>   | 30 minutes                 |

#### Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button on top of can and spray with button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.

### STORAGE:

**Ez Coat** should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Ez Coat** is 5 years when stored under normal conditions.

### RELATED PRODUCTS:

| <b>Part:</b> | <b>Product Name:</b>          | <b>Size:</b>   |
|--------------|-------------------------------|----------------|
| 38371        | SEM Solve                     | Gallon         |
| 38373        | SEM Solve                     | 20 oz. Aerosol |
| 38374        | SEM Solve                     | Quart          |
| 38375        | SEM Solve                     | 5 Gallon       |
| 77763        | XXX Universal Gun Cleaner     | 20 oz. Aerosol |
| 77771        | XXX Universal Surface Cleaner | Gallon         |
| 77774        | XXX Universal Surface Cleaner | Quart          |