



PBE GRAY FILLER PRIMER #20-1674

Seymour's Gray Filler Primer minimizes the appearance of deep surface scratches on metal surfaces. Durable and tough, it dries fast so you can form a thick, sandable base coat in no time. The large fan sprayhead eliminates the need for a spray gun on small repair jobs, and reduces your cleanup time.

Suggested Uses:

Fenders
Fiberglass body panels
Bumpers

Packaging:

UPC Code	043281002226
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.78
Solids Content	22%
MIR value	0.68, cannot exceed 0.80
HAPs content	3%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Nitrocellulose lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To topcoat	10 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter