



PROFESSIONAL AUTOMOTIVE SPECIAL SERVICE TOOLS
SIR TOOLS 
 MERCEDES - PORSCHE - BMW - VW - AUDI - VOLVO - SAAB - ASIAN

NEW TOOLS



Speed, Time, Distance- GT3 Cup Cars Set World Record!

Sir Tools congratulates and is a proud sponsor of team "Glenn Yee Motorsports" setting new world records. Two GT3 Porsches @ Thunderhill Raceway, California: #64 and #26, each hammering the field for 25 hours, 622 laps, 1866 miles with over 5000 passes, posting a 1st & 2nd place victory, respectively.

Good Luck @ Daytona, 24 hours!

From road to track, SIR TOOLS shines with over 30 years of expertise in manufacturing and designing special tools!

HO 115-WB **Honda / Acura Crank Seal Set:**



This Crank Shaft oil seal installation kit was specifically designed to aid the professional Honda / Acura Technician with the crucial task of proper and easy, harmonic balancer oil seal installation. The press cup is of a high quality anodized aluminum which will not damage the oil seal or engine. The threaded step bolt screws into the crank bolt hole. The press nut and washer provides the technician with an even and straight pressing force, seating the new oil seal into the engine case every time.

ST 9000 A **Anti-Theft Radio Key Kit:**



See World Exclusive Tool Kit #: ST 9015

This 6-pack wallet style O.E. radio removal kit is specially designed to remove all "Anti-Theft" radios from its mounting bracket. These O.E. anti-theft radios are found on late model to current 2004; VW, AUDI, Mercedes, Porsche, BMW, and many FORD based models. The most complete key kit, designed with ergonomically correct handles, most with vinyl coating, protecting your fingers.

ST 9006 **Master Blind Hole Bushing and Bearing Puller Master Set:**



This master set was developed to be the most extensive and professional (8) piece Blind Hole Bushing and Bearing Puller set ever assembled. All pieces of this master kit have their own compartment within in a storage case. The contents of which are as follows:

- (1) Slide Hammer Shaft Length with "T" Handle = 15.5" inches;
- (1) Hammer Weight = 2.15lbs with a Length of 4" inches;
- (8) Collets Size Range = mm (SAE); 8~10 [5/16~13/32"], 10~12 [13/32~15/32"], 12~14 [15/32~9/16"], 15~17 [19/32~11/16"], 17~20 [11/16~25/32"], 20~24 [25/32~15/16"], 25~29 [1~1-1/8"], 30~32 [13/16~11/4"]

ST0129 **Universal Asian Oil Seal Installation Bonus Kit:**



This Special Bonus Kit was designed for the proper installation of **crank shaft** oil seals, situated within confined areas on most 4, 6 & 8 cylinder Toyota / Lexus, Nissan, Mitsubishi, Mazda and Infiniti engines. Application includes **cam shaft** oil seal installation of Toyota / Lexus 2.5L, 2.8L, 3.0L, 3.4L, 4.0L & 4.3L engines. The step bolts screw into the cam or crank shaft end. The press nut w/ washer allows for an even pressing force, seating the oil seal into the engine case every time. See tool no. TOY 100 for (4) cylinder Asian cam shaft oil seal installation. Honda/Acura, see tool no's. HO 100, 105, 115 & 115-WB.

V 525 **Pressure Adaptor:**

Needed for pressurizing the master cylinder or clutch slave cylinder reservoirs. Used in conjunction with a pressure bleeder, 1/4-18 NPT threaded coupler.

Applicable: Volvo S40 & V40.

