



GET THE ORIGINAL

X2O GEN2 WIRELESS

WATERPROOF WINCH

SERIES WOUND AMPHIBIOUS TECHNOLOGY

		10,000 Lb features	12,000 Lb features	15,500 Lb features	17,500 Lb features
Waterproof		IP68 Rating	IP68 Rating	IP68 Rating	IP68 Rating
Rated Line Pull (Single)		10000 lbs (4535kgs)	12,000 lbs (5,454kgs)	15,500 lbs (7,045kgs)	17,500 lbs (7,954kgs)
Motor		6.6hp Series Wound	6.6hp Series Wound	6.6hp Series Wound	6.6hp Series Wound
Control Switch		Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead
Gear Train		3-Stage Planetary	3-Stage Planetary	3-Stage Planetary	3-Stage Planetary
Gear Ratio		218:1	265:1	430:1	430:1
Clutch		Sliding Ring Gear	Sliding Ring Gear	Sliding Ring Gear	Sliding Ring Gear
Brake		Automatic Out-Of-Drum	Automatic Out-Of-Drum	Automatic Out-Of-Drum	Automatic Out-Of-Drum
Drum Size		Diameter 2.5" (63.5mm)	Diameter 2.5" (63.5mm)	Diameter 3.45"(88.0mm)	Diameter 3.45"(88.0mm)
Length		10.0" (254mm)	10.0" (254mm)	10.0" (254mm)	10.0" (254mm)
Fairlead	X2O	4-Way Roller	4-Way Roller	4-Way Roller	4-Way Roller
	X2O COMP	Competition Aluminum	Competition Aluminum	n/a	n/a
Rope	X2O	Steel	Steel	Steel	Steel
	X2O COMP	Synthetic	Synthetic	n/a	n/a
Recommended Battery		650CCA Minimum for Winching	650CCA Minimum for Winching	650CCA Minimum for Winching	650CCA Minimum for Winching
Battery Leads		25mm2, 72"(1.83m)	25mm2, 72"(1.83m)	25mm2, 72"(1.83m)	25mm2, 72"(1.83m)
Finish		Textured Black	Textured Black	Textured Black	Textured Black
Weight		99.0 lbs (45.0Kgs)	99.0 lbs (45.0Kgs)	150.0 lbs (68.0Kgs)	150.0 lbs (68.0Kgs)
Mounting Bolt Pattern		10.0" x 4.50"	10.0" x 4.50"	10.0" x 4.50"	10.0" x 4.50"
Overall Dimensions		22.3" (L) x 5.4" (W) x 9.4" (H)	22.3" (L) x 5.4" (W) x 9.4" (H)	22.3" (L) x 7.5" (W) x 10.7" (H)	22.3" (L) x 7.5" (W) x 10.7" (H)
Cable Size		98.5' Length 3/8" Diameter	98.5' Length 3/8" Diameter	98.5' Length 7/16" Diameter	98.5' Length 1/2" Diameter
Mechanical Warranty		Lifetime Warranty	Lifetime Warranty	Lifetime Warranty	Lifetime Warranty
Electrical Warranty		5-Year Warranty	5-Year Warranty	5-Year Warranty	5-Year Warranty

Line Speed / AMP Draw (First Layer)

		10,000 Lb						12,000 Lb					15,500 Lb					17,500 Lb					
Line Pull	lbs	0	2000	4000	6000	8000	10000	0	3000	6000	9000	12000	0	4000	7500	11250	15500	0	6000	10000	12000	14000	17500
	kg	0	907	1814	2721	3628	4545	0	1363	2727	4090	5454	0	1814	3409	5113	7045	0	2721	4536	5454	6363	7937
Line Speed	ft/min	31.1	14.3	11.7	10.17	8.8	7.38	24.6	11.48	8.86	7.22	5.58	23.62	10.50	8.20	5.25	3.94	23.62	9.18	5.90	4.92	4.26	2.95
	m/min	9.5	4.3	3.5	3.2	2.7	2.25	7.5	3.5	2.7	2.2	1.7	7.2	3.2	2.5	1.6	1.2	7.2	2.8	1.8	1.5	1.3	0.9
Motor	Amps	76	150	220	270	320	380	70	138	218	260	330	71	152	239	332	422	71	200	300	350	395	450

Line Pull and Cable Capacity

		10,000 Lb				12,000 Lb				15,500 Lb				17,500 Lb			
Layers of cable		1	2	3	4	1	2	3	4	1	2	3	4	1	2	3	4
Rated line pull, Per layer	lbs	10000	9100	8570	7950	12000	9530	7929	6770	15500	12060	10082	8662	17500	15225	13246	11524
	kg	4545	3915	3499	3215	5455	4332	3604	3077	7045	5482	4583	3937	7955	6920	6021	5238
Cumulative cable	ft	19.6	44.2	73.8	98.4	18	37	64	98	19.68	45.92	75.44	85.28	19.68	45.92	75.44	85.28
Capacity	m	6	13	22	30	5.4	11.4	19.4	30	6	14	23	26	6	14	23	26

Part Numbers

	10,000 Lb	12,000 Lb	15,500 Lb	17,500 Lb
X2O Series	#97510	#97512	#97515	#97517
X2O COMP Series	#98510	#98512	n/a	n/a