

4500 Series LED Beacons



Flat/Pipe Mount Dome Size

4" **ELB45BCLØ(xx)**
6" **ELB45BCHØ(xx)**

Magnetic Mount Dome Size

4" **ELB45BML+(xx)**
6" **ELB45BMH+(xx)**

Replace (xx) in the Order Number for LED and Dome Color Selections

AA = Amber LEDs, Amber Dome
AC = Amber LEDs, Clear Dome
BC = Blue LEDs, Clear Dome
BB = Blue LEDs, Blue Dome

FC = Amber and White LEDs, Clear Dome
GC = Green LEDs, Clear Dome
GG = Green LEDs, Green Dome
JC = Red and Blue LEDs, Clear Dome (low dome only)

RC = Red LEDs, Clear Dome
RR = Red LEDs, Red Dome
WC = White LEDs, Clear Dome

Features

- Lens with UV inhibitor prevents sun fade
- Rated to last 20,000+ hours
- Heavy duty cast aluminum base
- SAE J845 Class 1 certified



Branch Guards and Dust Cover

Technical Specifications

INPUT VOLTAGE RANGE	10-30 Vdc
CURRENT DRAW	1 Amp @ 12 Vdc, 0.5 Amps @ 24 Vdc
LED COUNT	12 LEDs
FLASH PATTERNS	8 flash patterns
OPERATING TEMPERATURE	-40° C to + 65° C
DIMENSIONS	4" Dome with base Height: 5" (12 cm) Diameter: 6.3" (16 cm) base 6" Dome with base Height: 6.8" (17 cm) Diameter: 6.3" (16 cm) base
MOUNTS	Flat/Pipe or Magnetic mounts
CERTIFICATIONS	SAE J845 Class 1 certified
WARRANTY	Five-year

4800, 4500, 4200 LED and 3000 Strobe Series

accessories **Branch Guard and Dust Cover**

Beacons are sold separately.



Branch Guard

4" Height
6" Height (shown)

#PESB41BG4

#PESB41BG6



Dust Cover

6" Height

E36ØDC6