

## **PRODUCT DATA SHEET**

New Generation™ Wheel Bearing Grease for Disc and Drum Brakes, 7 Lbs (Discontinued)

Part Number: SL3116

Product Description A premium lithium complex NLGI grade 2 grease with

drop point of over 500° F. This grease is designed for late model vehicles wheel bearings, chassis, suspension & u-joints. Wide temperature range -40°F to 400°F. Extreme

pressure additives.

Product Discontinued

Applications Automotive applications, ball joints, bearings, chassis

points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides,

wheel bearings

Unit Package Description 7 Pound Pail

Brand Sta-Lube

Generic Description 1 Wheel Bearing Grease

Net Fill 7 Lb

UPC Code 072213311600

Unit Dimensions 7.75H x 7.5W x 7.5D in

Units Per Case 4

Case Dimensions 8H x 16.5W x 16.5D in

Cases Per Pallet 54
Case Weight 33 lbs

I 2 of 5 Code 30072213311601

Appearance Amber Semi-Solid to Solid Grease

Base Type Polyalphaolephin & Pentaerythritol Esters w/ fumed silica

Flash point (F) 450°F Flash point (C) 232°C

Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 2


Timken OK Load [Lbs.] 50 Lbs

Plastic Safe Not Determined

Last revised: 5/4/2016

Page 1 of 2







## **PRODUCT DATA SHEET**

Evaporation Rate <1 (butyl acetate=1)

Working Temp (F) -40 to 400°F

Working Temp (C) -40 to 176.7°C

4 Ball EP 45 LWI

4 Ball Wear Not Determined

Drop Point 500°F Leakage 10g Max

Oil Separation <10%
ISO Viscosity Grade 150

Water Washout <15%

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Federal) 1
VOC g/L (Federal) 9

VOC Lbs./Gal. (Federal) 0.075

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 5/4/2016

Page 2 of 2



Product

Discontinued