



PRODUCT DATA SHEET

Moly-Graph Extreme Pressure Multi-Purpose Grease, 35 Lbs

Part Number: SL3145



Product Description

Extreme pressure MOLY-GRAPH Multi-Purpose Grease is the best general purpose grease for a wide range of applications. It offers an excellent mechanical and shear stable Lithium 12 Hydroxy Protection of "moly" and graphite. Timken load of 40 lbs.

Applications

Automotive applications, backing plates, ball joints, chassis points, construction ball & roller bearings, idler bearings, industrial applications, mining applications, pillow block bearings, sprocket bearings, U-joints, water pumps, wheel bearings

Unit Package Description

35 Pound Pail

Brand

Sta-Lube

Generic Description 1

E. P. Multi-Purpose Lithium Grease

Net Fill

35 Lb

UPC Code

072213314502

Unit Dimensions

14.5H x 12W x 12D in

Units Per Case

1

Case Dimensions

14.5H x 12W x 12D in

Cases Per Pallet

36

Case Weight

40 lbs

Appearance

Dark Gray Semi-Solid to Solid Grease

Base Type

Lithium-12

Flash point (F)

>400°F

Flash point (C)

>204°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

45 Lbs Min

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Last revised: 5/4/2016

Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (F)	-25 to 250°F
Working Temp (C)	-31.7 to 121°C
4 Ball EP	250 KG Weld, 30 LWI
4 Ball Wear	0.6 mm typical
Drop Point	350°F
Elastomer Compatibility	0 to 40% vol ; 0 to 15 hard
Leakage	5
Oil Separation	10
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.8°C
ISO Viscosity Grade	165
Water Washout	10
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0.2
VOC g/L (Federal)	1.8
VOC Lbs./Gal. (Federal)	0.015
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 5/4/2016
Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.