



**NOTE:**

- 1) INSTRUCTION SHEET P/N PLITSTR383
- 2) PACKING: P/N SCART200Z  
INCLUDES:  
(1) UNIT BOX P/N PCARTZFOLDU  
(1) 10 x 12 POLY BAG P/N P30024-14
- $\triangle B$  3) BOX LABEL BLANK P/N PLAB64
- 4) LENS COLORS: AMBER, CLEAR  
\* = A, C
- 5) VOLTAGES:  
201ZL (10-16V DC) (0.35 Amps @ 10V-16V DC)  
 $\triangle B$  201ZL-110 (10V-110V DC)(0.13 Amps @ 10V-110V DC)

**SPECIFICATIONS  $\triangle B$**

Typical Input Voltage Range: 10-16VDC  
 Typical Current Draw: .35A @ 12VDC  
 Flash Rate: Single Flash 65sfpm  
 Output Power: Single Flash 3.1W  
 Connections: 18" Min. wires exiting the unit.  
 Permanent Mounting: 2 Holes on  $\phi$ 2.75 Center  
 Dimensions (Short Dome): 4.25" tall x  $\phi$ 2.75".  
 Individual Shipping weight: 1.5 lbs.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES Drill Tolerances $\pm$ 0.003 Artwork and board size TOLERANCES: ANGULAR: $\pm$ 2 DEG. .X $\pm$ .100 .XX $\pm$ .020 .XXX $\pm$ .005 .XXXX $\pm$ .001	DRAWN BY: TM/DPL	<b>STAR HEADLIGHT &amp; LANTERN CO., INC.</b>	
RoHS COMPLIANT: NA			
MATERIAL: NA		TITLE: MODEL DRAWING	DWG. NO. 201ZL
FINISH: NA	SCALE: 1:1	DO NOT SCALE FROM DRAWING	SHEET 1 OF 1