



**NOTE:**

- 1) INSTRUCTION SHEET P/N PLITSTR43
- 2) PACKING INCLUDES: SCART4000  
 (1) UNIT BOX P/N PCART4000 UN  
 (1) UNIT BOX INSERT P/N PCART4000CS  
 (1) 12 x 16 POLY BAG P/N P30024-12
- 3) BOX LABEL BLANK P/N PLAB64
- 4) LENS COLORS: AMBER, BLUE, CLEAR, GREEN, RED
- 5) \* = A, B, C, R (SAE J578)

Typical Input Voltage Range: 10-30 VDC  
 Typical Current Draw: 2.0 A @ 12VDC  
 Approval: S/D SAE J1318 Class 2 Amber,Blue,Clear,Red  
 Quad SAE J1318 Class 1 Amber,Clear,Blue,  
 SAE J1318 Class2 Red.  
 Flash Rate: S/D/Q 100fpm/65dfpm/75qfpm respectively  
 Output Power: S/D/Q 24W/18.7W/24W respectively  
 Connections: 18"Min. wires exiting the unit.  
 Permanent Mounting: 2 Hole 4.50" center  
 Dimensions: (Tall Dome): 6.00" tall x Ø5.50".  
 Individual Shipping weight: 3.0 lbs.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES Drill Tolerances ± 0.003  Artwork and board size TOLERANCES: ANGULAR: ± 2 DEG. .X ± .100 .XX ± .020 .XXX ± .005 .XXXX ± .001	DRAWN BY: DPL	<b>STAR HEADLIGHT &amp; LANTERN CO., INC.</b>	
	DRAWING APPROVED BY ECR		
ROHS COMPLIANT: NA		MODEL: 240C-12V-* (12/24VDC, S/D/Q FLSH)	
MATERIAL: NA		TITLE: MODEL DRAWING S/D/Q FLASH STROBE	
FINISH: NA	DWG. NO. 240C	REV C	
	SCALE: 1:1	DO NOT SCALE FROM DRAWING	SHEET 1 OF 1

**Star Headlight provides the best in emergency and warning lighting equipment.**