

10608

# Wheel Stud Press

Commercial Hydraulic Drum

## // Safety Warning

**Read all instructions and safety warnings prior to operation.**

**Failure to do so could result in equipment damage, personal injury, or even death.**

**CAUTION:** Use replacement parts and accessories provided by tiger tool only. All replacement parts and accessories are available. Keep hydraulic coupler protected when not in use. Dust caps should be used on couplers when not in use to avoid contaminants from entering the hydraulic cylinder and power source. This practice will help to extend the life of this product and ensure continued consistent operation.

- Stay Alert! Watch what you are doing and use common sense when operating this tool.
- Inspect product for damage prior to using; do not use if product is in unsafe condition.
- Do not operate tool while under the influence of drugs, alcohol, or medication.
- Always use safety equipment to prevent injuries. Approved face and eye protection must always be worn by the operator, as well as others in the work area.
- Do not overreach. Keep proper footing and balance at all times.
- Dress properly. Do not wear loose clothing or jewelry.
- Keep your hair, clothing and gloves away from moving parts.
- Keep hands clear of all pressurized hydraulic components.
- Always ensure hoses are free from sharp bends and kinks.
- Keep your work area clean and well lit.
- Cylinders are designed for 10,000 psi (700 bar) maximum working pressure. Do not connect to a pump with a higher rated pressure. Use a pressure gauge in the system at all times. Ensure all components in the system are rated for 10,000 psi (700 bar).

# Operating Instructions

**NOTE:** Hammering this tool will void your warranty.

## Wheel Stud Removal

- 1 Thread the 10 ton cylinder into the threaded end of the C-frame.
- 2 Attach the hydraulic power supply to the cylinder (Use any 10,000 psi air/hydraulic pump).
- 3 Install the appropriate stud removal adaptor into the opposing end of the C-frame. **(Figure 1)**
- 4 Select the appropriate stud pusher adaptor (long or short, depending on stud length) and thread into the hydraulic cylinder. **(Figure 2)**
- 5 Position the 10608 over the wheel stud and apply hydraulic pressure until the wheel stud is released from the hub flange. **(Figure 3)**
- 6 Upon removal of all wheel studs, remove the removal adapters from the hydraulic cylinder and opposing end of the C-frame to prepare for installation.


1



2



3



# Operating Instructions



## Wheel Stud Installation

**NOTE:** Thoroughly remove any corrosion, rust or burrs from the rear side of the hub to ensure proper wheel stud installation.


- 1** Select the threaded installation anvil from the kit and thread it into the hydraulic cylinder. **(Figure 1)**
- 2** Insert the installation adapter into the opposing C-frame. **(Figure 2)**
- 3** Insert the new wheel stud through the backside of the hub by hand.
- 4** For installation of 3/4" or 22 mm studs you must select the appropriate aluminum sleeve and place it over the protruding threaded area of the stud **(Figure 3)**. Then place the installation tube housing over the aluminum installation sleeve.

For installation of 1 1/8" studs the aluminum sleeve is not required. Use the installation tube housing only.

- 5** Position the 10608 over the wheel stud/installation tube and continue to apply hydraulic pressure until the stud is securely seated into the hub flange. **(Figure 4)**



# Parts Breakdown



| Part Number    | Description                                    | Qty. |
|----------------|--|------|
| H1004 (RCH104) | 10 Ton Hollow Cylinder                         | 1    |
| 70250-1        | Female Coupler                                 | 1    |
| 10608-18       | Installation Tube                              | 1    |
| 10608-6        | Stud Remover Anvil – Long                      | 1    |
| 10608-4        | Stud Install Anvil                             | 1    |
| 10608-7        | Stud Removal Adaptor – Through Hole – 1.4" Dia | 1    |
| 10608-3        | Stud Installer Base 1 1/8"                     | 1    |
| 10608-12       | O-Ring   | 4    |
| 10608-8        | Stud Remover Anvil – Short                     | 1    |
| 70250-2        | Male Coupler                                   | 1    |
| 10608-21       | 3/4" Reducer Sleeve                            | 1    |
| 10608-22       | 22mm Reducer Sleeve                            | 1    |
| 10608-1        | Frame  | 1    |
| 10608-5        | Stud Installer – Long                          | 1    |