

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

* 1 Identification

- **Product identifier**
- **Trade name: Flammable Rubber Cement**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Plews, Inc.
- **Emergency telephone number:**
For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08



GHS09

- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 1)

· **Hazard-determining components of labeling:**

n-heptane

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Avoid release to the environment.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMSI-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 1 | Health = 1 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 2)

| · Dangerous Components: | | |
|--------------------------------|--|--------|
| 142-82-5 | n-heptane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 80-90% |
| 9006-04-6 | Natural rubber latex | 5-15% |

* 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get immediate medical attention.

In case of unconsciousness, place patient securely on side position for transportation.

· **After skin contact:**

Immediately wash skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. Wash clothing before reuse. Get medical attention if symptoms occur.

· **After eye contact:**

Hold eyelids apart and flush eyes with plenty of water for at least 20 minutes.

Seek medical treatment.

· **After swallowing:**

Seek immediate medical advice.

Do not induce vomiting without medical advice.

Do not induce vomiting without medical advice.

Get medical attention.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

May produce incomplete combustion products (CO, CO₂).

· **Advice for firefighters**

· **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

* 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Use the appropriate tools to collect the material and dispose of it in an approved waste disposal container.

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 3)

- Do not flush with water or aqueous cleansing agents
- Dispose of the collected material according to regulations.
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

* 7 Handling and storage

- **Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
- Keep ignition sources away - Do not smoke.
- Protect from heat.
- Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with occupational exposure limits:**

142-82-5 n-heptane

| | |
|-----|---|
| PEL | Long-term value: 2000 mg/m ³ , 500 ppm |
| REL | Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min |
| TLV | Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm |

9006-04-6 Natural rubber latex

| | |
|-----|--|
| TLV | Long-term value: 0.0001* mg/m ³ Skin; DSEN, RSEN,* inh. fraction |
|-----|--|

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 4)

- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

* 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

| | |
|------------------------|-----------------|
| Form: | Pasty |
| Color: | Light yellow |
| Odor: | Gasoline-like |
| Odor threshold: | Not determined. |

- **pH-value:** Not determined.

- **Change in condition**

| | |
|-------------------------------------|-----------------|
| Melting point/Melting range: | Not determined. |
| Boiling point/Boiling range: | 98 °C (208 °F) |

- **Flash point:** -4 °C (25 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 215 °C (419 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 1.1 Vol % |
| Upper: | 6.7 Vol % |

- **Vapor pressure @ 20 °C (68 °F):** 48 hPa (36 mm Hg)

- **Density:**

| | |
|-------------------------|-----------------|
| Relative density | Not determined. |
| Vapour density | Not determined. |

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 5)

- | | |
|---|--|
| Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 80-90 % |
| VOC content: | 80-90 % |
| · Other information | No further relevant information available. |

*** 10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Carbon dioxide and carbon monoxide may form when heated to decomposition
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*** 11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
None of the ingredients are listed.

| |
|--|
| Group 1 - Carcinogenic to humans |
| Group 2A - Probably carcinogenic to humans |
| Group 2B - Possibly carcinogenic to humans |
| Group 3 - Not classifiable as to its carcinogenicity to humans |
| Group 4 - Probably not carcinogenic to humans |

· **NTP (National Toxicology Program)**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 6)

*** 12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

*** 13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**
Observe all federal, state and local environmental regulations when disposing of this material.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*** 14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN2278
- **UN proper shipping name**
- **DOT** N-Heptene
- **ADR** UN2278 n-Heptene, mixture, ENVIRONMENTALLY HAZARDOUS
- **IMDG** N- HEPTENE, mixture, MARINE POLLUTANT
- **IATA** N- HEPTENE, mixture
- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 7)

· **Label** 3· **ADR**· **Class** 3 (F1) Flammable liquids· **Label** 3· **IMDG**· **Class** 3 Flammable liquids· **Label** 3· **IATA**· **Class** 3 Flammable liquids· **Label** 3· **Packing group**· **DOT, ADR, IMDG, IATA** II· **Environmental hazards:** Product contains environmentally hazardous substances: n-heptane· **Marine pollutant:** Yes· **Special marking (ADR):** Symbol (fish and tree)· **Special precautions for user** Symbol (fish and tree)· **Danger code (Kemler):** Warning: Flammable liquids· **EMS Number:** 33· **Transport in bulk according to Annex II of** F-E,S-D· **MARPOL73/78 and the IBC Code** Not applicable.· **Transport/Additional information:**· **DOT**· **Quantity limitations** On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Remarks:** ERG Number: 128· **ADR**· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml· **IMDG**· **Limited quantities (LQ)** 1L

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 8)

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN2278, n-Heptene, mixture, ENVIRONMENTALLY HAZARDOUS, 3, II

* 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

142-82-5 | n-heptane

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

142-82-5 | n-heptane

D

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

n-heptane

· **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 9)

Causes skin irritation.
 May cause drowsiness or dizziness.
 May be fatal if swallowed and enters airways.
 Very toxic to aquatic life.
 Very toxic to aquatic life with long lasting effects.





Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves / eye protection / face protection.
 Wear protective gloves.
 Ground/bond container and receiving equipment.
 Use only non-sparking tools.
 Avoid release to the environment.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 If swallowed: Immediately call a poison center/doctor.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 Specific treatment (see on this label).
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO2, powder or water spray.
 Collect spillage.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

State Right to Know

| | |
|-----------------------------|---|
| 142-82-5 | n-heptane |
| |  Flam. Liq. 2, H225;  Asp. Tox. 1, H304;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Irrit. 2, H315; STOT SE 3, H336 |
| 9006-04-6 | Natural rubber latex |
| All ingredients are listed. | |

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Trade name: Flammable Rubber Cement

(Contd. of page 10)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

· *** Data compared to the previous version altered.**