



VALVOLINE™ DURABLEND™ GEAR OIL

Valvoline DuraBlend Gear Oils are outstanding partial-synthetic sulfur-phosphorus, extreme pressure gear lubricants. They provide enhanced performance in both low and high-temperature operating conditions. These products are recommended for conventional rear axles, and transmissions requiring EP gear lubes under high speed, high load, high torque, high horsepower conditions.

The Valvoline DuraBlend Oil Advantages:

- **Thermal Protection:** Provides outstanding thermal stability for cleanliness and longer service life.
- **Wide operation temperature range:** Provides enhanced performance in both low and high temperature operating conditions.
- **Wear Protection:** Contains additives to assist in protecting gear teeth against pitting, spalling, and scouring.
- **Corrosion Protection:** Protects parts from rust and corrosion.

Approvals/Performance Levels

API GL-4 *	80W-90	85W-140
API GL-5	80W-90	85W-140

Typical Properties

	80W-90	85W-140
Vis @ 100 °C (cSt)	14.5	28.5
Vis @ 40 °C (cSt)	133	331
Viscosity Index	109	117
Density (lbs/gal)	7.37	7.44
Brookfield Vis., cP	98,000(-26°C)	30,000(-12°C)
Pour Point, °C	-27	-18
Phosphorus, wt%	0.054	0.054

*In synchronized manual transmission applications use:

- Valvoline Professional Series Manual Transmission Fluid or
- Valvoline Synchronmesh Manual Transmission Fluid (available September 2012)

Effective Date: 06/01/2017

Replaces: 05/21/2012

KD