Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ SAE 80W-90

HP GEAR OIL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Contaminated work clothing must not be allowed out of the

workplace.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Tiuzui uouo oompononto			
Chemical name	CAS-No.	Classification	Concentration (%)
OLEFINSULFIDE	68937-96-2	Skin Sens. 1B; H317	2.5335
React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		Flam. Liq. 4; H227 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317	0.6428

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction. No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons Sulphur oxides

Specific extinguishing

methods

.

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Components	CAS-No.
OLEFINSULFIDE	68937-96-2
React. prod. of bis(2-	
methylpentan-2-	
yl)dithiophosphoricacid +	
phosphorus oxide, propylene	
oxide and amines, C12-14-alkyl	
(branched)	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions

of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 424.9 °F / 218.3 °C

(1013.333 hPa)

Flash point : $> 432 \,^{\circ}\text{F} / > 222 \,^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : > 1

Ethyl Ether

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.1000000 mmHg

Relative vapour density : > 1AIR=1

Relative density : 0.89 (60.00 °F)

Density : 0.8916 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 146 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Sodium oxides

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

<u>Components:</u> OLEFINSULFIDE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is classified as acute

oral toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

OLEFINSULFIDE:

Result: Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Remarks: Unlikely to cause eye irritation or injury.

Components:

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

OLEFINSULFIDE:

Result: Slight, transient irritation

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

<u>Components:</u> OLEFINSULFIDE:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 406

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Test Type: Local lymph node assay

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

<u>Components:</u> OLEFINSULFIDE:

Genotoxicity in vitro : Test Type: in vitro assay

Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Cell type: Bone marrow

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

OLEFINSULFIDE:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Water flea (Daphnia magna)): ca. 91.4 mg/l

Exposure time: 48 h Test Type: static test

Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 15

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

mg/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3

mg/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Water flea (Daphnia magna)): 0.12 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

<u>Components:</u> OLEFINSULFIDE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 13 % Exposure time: 28 d

Method: OECD Test Guideline 301B

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 7.4 % Exposure time: 28 d

Method: Modified Sturm Test

No data available

Bioaccumulative potential

Components:

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n- : Remarks: No data available

octanol/water

No data available **Mobility in soil Components:**

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods
Not dangerous goods

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

0.5. DOI - INCAND WATERWATE				
Not dangerous goods				

TDG_ROAD_C

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

	Not dangerous goods
TDG_RAIL_C	
	Not dangerous goods
TDG_INWT_C	
	Not dangerous goods
INTERNATIONAL	MARITIME DANGEROUS GOODS
	Not dangerous goods
INTERNATIONAL	_ AIR TRANSPORT ASSOCIATION - CARGO
	Not dangerous goods
INTERNATIONAL	AIR TRANSPORT ASSOCIATION - PASSENGER
	Not dangerous goods
	Not dangerous goods

Not dangerous goods

MX_DG

Marine pollutant	no	
		i

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ. **SARA 304 Extremely Hazardous Substances Reportable Quantity**This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/05/2017



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H227 Combustible liquid.

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

Valvoline.	Page: 15
SAFETY DATA SHEET	Revision Date: 06/05/2017
	Print Date: 4/5/2018
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL	Version: 1.8
VV831	

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System