



Safety Data Sheet

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System
Date of Revision: 02/06/2020 Revision: 01

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **Classic Hi-Performance API GL-4 Gear Oil SAE 80W-90**

12 Synonym: Blend

1.2 VP Racing Fuels, Inc.

1.3 Recommended Use: Yellow Metals in Classic Manual Transmissions and Transaxles

1.4 **RESTRICTIONS on USE Applications Requiring a GL-5 Extreme Pressure or other Gear Oil Quality; or OEM Specialized Lubricant.**

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Hazard Categories

Eye Irritation

Category 2A

Skin Irritation

Category 2

Skin Sensitization

Category 1

Reproductive Toxicity

Category 2

Specific Target Organs toxicity repeated exposure

Category 2

Harmful to Aquatic Life with Long Lasting Effects

Category 3

2.2 Signal Word: **Warning**



2.3 Pictograms:

Health

Irritant

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

2.4 Hazard Statements

PHYSICAL HAZARDS:	None
HEALTH HAZARDS	H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H361: Suspected of damaging fertility or the unborn child. H373: May cause damage to organs through prolonged or repeated exposure.
ENVIRONMENTAL HAZARDS:	H412: Harmful to aquatic life with long-lasting effects.
PRECAUTIONARY STATEMENTS:	P102: Keep out of reach of children. P201: Obtain special instructions before use. READ SDS BEFORE USE. P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing mist. P264: Wash hands through after handling. P270: Do not eat, drink, or smoke when using this product. P272: Contaminated work clothing should not be allowed out of the workplace. P373: Avoid release to the environment. P280: Wear protective gloves, clothing, and eye protection.
RESPONSE STATEMENTS:	P303+P361+353: IF ON SKIN Take off immediately all contaminated clothing, rinse skin with water. P305+P351: IF IN EYES. Rinse cautiously with water for at least 15 minutes. If present, remove contact lenses if easy to do so. P308+P313: If exposed or concerned, get medical attention. P313+P337: If eye irritation persists, get medical attention. P313+P332+P333: If skin irritation or rash occurs, get medical attention. H314: Get medical attention if you feel unwell. P362+P364: Take off contaminated clothing and wash them before reuse.
STORAGE STATEMENTS:	P405: Store lock up

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Classic Hi-Performance gear oil with Additives	100 %	None

3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	Carc. 1B H350
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	Carc. 1B H350
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361, STOT RE 2 H373
Mineral oil	64742-53-6	265-156-6	Carc. 1B H350
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	270-128-1	Aquatic Chronic 3 H412
Benzothiazole-2-thiol	149-30-4	205-736-8	Skin Sens.1 H317, Aquatic acute H400, Aquatic Chronic H410

3.3 Trade Secret Provision and Chemical Concentration Disclosure: Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and apply to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can irritate. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause irritation, defatting, and drying of the skin.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

4.3 Ingestion: Causes headache, gastrointestinal pain, nausea, and. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following exposure may be more related to the time between exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam

5.4 Fire Fighting Equipment/Instructions: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Evacuate area. Only trained and properly protected personnel must be involved in clean-up operations. Keep upwind of a spill. Ventilate area of leak or spill.

6.2 Spills: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep the container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container locked up.

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Classic Hi Performance gear oil with Additives	5mg/m3 TWA	5mg/m3 TWA

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Dark

Odor: Aromatic Hydrocarbon

Vapor Pressure: 45 mmHg@21°C

Vapor Density (Air=1): Not Available

Specific Gravity (H₂O=1,): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not Applicable

Evaporation rate: Not Available

Partition coefficient octanol/water: 2 to 6

Water Solubility: Insoluble

Flash Point: 561°F, 293.8 °C close cup

Boiling Point: 600-1200 °F, 315.5-648-8 °C

Freezing/Melting Point: Not Available

LEL: Not Applicable

UEL: Not Applicable

Viscosity: Kinematic 143 cm²/s@104°F,40°C

Autoignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): >2000 mg/kg

ATE (Dermal): >2000 mg/kg

ATE (Inhalation vapor/mist): >20 mg/l

11.1.1 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Harmful Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Harmful Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Harmful Inhalation Toxicity.

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

11.2 Route of Entry: Ingestion, Absorption, Skin and Eye Contact

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that no components of this product may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause eye irritation.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency DataBase show components of this product to cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): None shown

11.11 Target Organ Toxicity (Repeated Exposure): Contains material which may cause damage to the following organs: Eyes and skin.

11.12 Signs and Symptoms: Effects may include: Headache, Dizziness, Drowsiness. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause cancer, however, by test contains <3% DMSO extract per IP346 and is not considered to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Classic Hi-Performance gear oil with Additives	Not listed	Not listed	Not listed	Not listed

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Classic Hi-Performance gear oil with Additives	Expected to be Harmful to aquatic organisms. May cause long-term adverse effects in the environment		

Toxicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause long-term toxicity to aquatic life.

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information
Not Regulated

14.2 IMDG Transport Information
Not Regulated

14.3 UN Dangerous Goods Transport Information
Not Regulated

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

Toxic Release Inventory (TRI): This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
108-88-3	Phenylmethane	At demines% limits
140-88-5	Ethyl acrylate	At demines% limits

This information must be included in all SDSs that are copied and distributed for this material.

CERCLA Hazardous Substances and corresponding RQs: Phenylmethane 1000 pounds. Ethyl acrylate 1000 pounds.

SARA Community Right-to-Know Program: All components of this blend.

Clean Water Act: None

Clean Air Act: None

Classic Hi Performance API GL-4 Gear Oil SAE 80W-90

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

OSHA: All ingredients are regulated by 29 CFR 1910.1200

State Regulations

California prop. 65:



WARNING-Cancer and Reproductive Harm - www.P65Warnings.ca.gov.”

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements

Pennsylvania: All components of this product) are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 International Regulations:

Australian Inventory of Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product are on the Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium database of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency DataBase Chinese Data Base Classification Labeling of Hazardous Chemicals, Australia Data Base for GHS Chemical Classification and MSDS and SDS of chemicals in this mixture.