

4

3

2

1

FRONT

BACK

PARA IMPORTADOR VEA PRODUCTO

**Conexion**  
Se sugiere fuertemente soldar los alambres del conector nuevo a los alambres del arnes del vehiculo con soldadura Rosin y forrados con tubo encogible aislante. Cualquiera otro tipo de reparacion solo es temporal. Asegúrese de empalmar cada alambre 1 al conector nuevo en la misma posición que tenía en el conector que fallo.

**Reemplazo del conector**  
Los colores de los alambres del conector podrian no coincidir con los de su vehiculo, pero si conecta al componente, es el correcto.

**LEA LAS INSTRUCCIONES ANTES DE LA INSTALACION.**

**Connection**  
It is strongly suggested to solder the new pigtail wires to the vehicle harness wires utilizing Rosin Core solder and shrink tubing; any other connection is only a temporary repair. Be certain to connect each wire of the new pigtail in the same location as the failed connector.

**Pigtail Replacement**  
The wire colors of this pigtail may not match the wire colors on your vehicle. If the connector plugs into the component, the pigtail is correct.

**PLEASE READ THE FOLLOWING INSTRUCTIONS BEFORE INSTALLATION.**



990701170

2.50

7.00

KEY CHARACTERISTIC		KPC/KCC 0 TOTAL 0 LAST NO. USED		SC 0 TOTAL 0 LAST NO. USED	
DATE	7/10/2018	SCALE	NTS	DRAWN BY	SAM
MATERIAL	20# WHITE SULFIDE PAPER		ENGINEER	TDS	
FINISH	BLACK PRINT DUPLEX		TITLE	INSTRUCTION SHEET	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES ANGLE ± 1° .XX ± .015 .XXX ± .005 GD&T ASME Y14.5-2009	 THIRD ANGLE		TYPE	SIZE	SHEET
				B	1 OF 1
			MODEL	PART NO.	REV
				990701170	-

REV.	DESCRIPTION	ECN	DATE	BY
-	RELEASED	43810	7/10/2018	SAM

REVISION

4 FOLDS 2.5 X 1.0