

4

3

2

1

FRONT

BACK

PLEASE READ THE FOLLOWING INSTRUCTIONS BEFORE INSTALLATION.

Pigtail Replacement
The wire colors of this pigtail may not match the wire colors on your vehicle. If the connector plugs into the component, the pigtail is correct.

Connection
It is strongly suggested to solder the new pigtail wires to the vehicle harness wires utilizing Roblin Core solder and shrink tubing; any other connection is only a temporary repair. Be certain to connect each wire of the new pigtail in the same location as the failed connector.



2.50

7.00

KEY CHARACTERISTIC		⊙ KPC/KCC 0 TOTAL 0 LAST NO. USED		○ SC 0 TOTAL 0 LAST NO. USED	
DATE	7/10/2018	SCALE	NTS	DRAWN BY	SAM
MATERIAL	20# WHITE SULFIDE PAPER		ENGINEER	TDS	
FINISH	BLACK PRINT DUPLEX		TITLE		
UNLESS OTHERWISE SPECIFIED DIM ARE IN INCHES ANGLE p 14 .XX p .015 .XXX p .005 GD&T ASME Y14.5-2009			THIRD ANGLE		TYPE
REV.		DESCRPTION	ECN	DATE	BY
-		RELEASED	43810	7/10/2018	SAM
-		REVISION			
MODEL		SIZE	B	SHEET	1 OF 1
PART NO.		990701170		REV	-



INSTRUCTION SHEET

990701170

4 FOLDS 2.5 X 1.0