



**REAL POWER
UNREAL PERFORMANCE**

REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Performance and Racing Products at 4XSPower.COM



S375 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 190A RC : 25min.

L: 7.87"(200mm) W: 3.03"(77mm) H: 5.43"(138mm)

Weight: 12.24lbs (5.55kg)



S545 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 240A RC : 15min.

L: 6.97"(177.03mm) W: 3.38"(85.8mm) H: 5.14"(130.55mm)

Weight: 11.01lbs (5.0kg)



S680 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 1000 CA : 320A RC : 28min.

L: 7.13"(181mm) W: 3.03"(77mm) H: 6.57"(167mm)

Weight: 15.42lbs (7.0kg)



S925 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 550A RC : 55min.

L: 6.5"(165.1mm) W: 6.93"(176.02mm) H: 4.92"(124.96mm)

Weight: 23.54lbs (10.7kg)



S975 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2100 CA : 525A RC : 50min.

L: 7.83"(198.88mm) W: 5.3"(134.62mm) H: 6.67"(169.42mm)

Weight: 26.43lbs (12kg)



S1200 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2600 CA : 725A RC : 80min.

L: 7.8"(198.1mm) W: 6.54"(166.1mm) H: 6.69"(169.92mm)

Weight: 33.26lbs (15.1kg)

BILLET AND STAMPED ALUMINUM HOLD DOWNS

Check Out The Entire Line of Corrosion Resistant, XS Power Billet and Stamped Aluminum Hold Downs at 4XSPower.COM



535

* NHRA APPROVED

975 billet aluminum hold down



573

* NHRA APPROVED

3400/1400/1600 billet aluminum hold down



514

545 series stamped aluminum side mount box without window



527

S925 stamped aluminum GM direct mount and universal mounting kit

12V / 14V / 16V AGM RACING POWER CELLS



S3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300 CA : 1000A RC : 135min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.88mm)
Weight: 46.0lbs (20.85kg)



D1400 / 14V AGM

14 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A Ah : 50

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.87mm)
Weight: 43.56lbs (19.75kg)



S1600 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 500A RC : 50min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 30.5lbs (13.9kg)



XP 1000 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 46.5lbs (21.1kg)



D1600 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A RC : 85min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 48.18lbs (21.85kg)

TAKE CONTROL OF YOUR CHARGING SYSTEM



VCM / Voltage Control Module

Precision Charging for 12V, 14V and 16V
Digital Dash-Mount Control
Backlit Bright/Dim Display
Plug & Play Installation

WHY DID WE DESIGN A 14V BATTERY YOU ASK?

Because after years of studying and listening to the feedback from racers we realized that an intermediate step was needed between 12V and 16V batteries. We have found that there are many advantages the 14V battery offers to the racer who also drives their race car on the street. Since 14V batteries need to be charged at 16.8V, we have also introduced the all new **Voltage Control Module (VCM)** that very simply plugs into the factory or aftermarket alternator to allow it to charge at the appropriate voltage for the 14V battery. With a 16V battery, the alternator charge voltage would need to be 19.2V, which is too high for many of the sensitive electronics that may be present in a street and strip race car.

IT'S LIKE 16V FOR THE STREETS!

GENUINE XS POWER CHARGERS AND ACCESSORIES



HF1615

*240V models available upon request

Compact High Frequency AGM IntelliCHARGER
15AMP Max Output. 12V, 14V and 16V Models Available



1004

16V AGM IntelliCHARGER - 20AMP Max Output



1005

*1005E model not shown, is 110V & 240V switchable

12V, 14V and 16V AGM IntelliCHARGER, Compatible 5A, 15A and 25A (25AMP Max Output), Three Charging Modes



PSC IntelliSUPPLY

*15A, 30A and 60A Models Available

12V, 14V and 16V Compact High Frequency IntelliSUPPLY with AGM charge mode. 30A & 60A Models are 110V/240V compatible.



551

I-Bar Kit, Side and Top Terminal Adaptors



993

Compact Voltage Step-Down Module - 25AMP Continuous, 50AMP MAX Output



Kit Contents

1qty - 16ft 2AWG XP FLEX RD Power Cable
1qty - 3ft 2AWG XP FLEX BK Ground Cable
8qty - XS Power Brand Heat Shrink
8qty - 2AWG Crimp Terminals
2qty - Battery Clamps
2qty - Grommets
10qty - Wire Clamps
10qty - Self Tapping Screws



RK2GA-1

XP FLEX, 2AWG, Single Battery, Light-Weight Racing Battery Relocation Wiring Kit



Kit Contents

1qty - 22ft 2AWG XP FLEX RD Power Cable
1qty - 6ft 2AWG XP FLEX BK Ground Cable
14qty - XS Power Brand Heat Shrink
14qty - 2AWG Crimp Terminals
4qty - Battery Clamps
4qty - Grommets
14qty - Wire Clamps
14qty - Self Tapping Screws



RK2GA-2

XP FLEX, 2AWG, Dual Battery, Light-Weight Racing Battery Relocation Wiring Kit